

Unit combination restrictions		Power supply					COMP		OFM		IFM	
Outdoor unit	Indoor unit	①	②	③	MCA	MFA	RHz	RLA	kW	FLA	kW	FLA
RXA20A5V1B	FTXA20A2V1B	50	220	MAX. 50Hz 264V	9,90	10	35	1,9	0,023	0,23	0,035	0,30
		50	230					1,8				
		50	240	MIN. 50Hz				1,7				
RXA25A5V1B	FTXA25A2V1B	50	220	MAX. 50Hz 264V	11,00	13	44	2,2	0,023	0,23	0,038	0,40
		50	230					2,1				
		50	240	MIN. 50Hz				2,1				
RXA35A5V1B	FTXA35A2V1B	50	220	MAX. 50Hz 264V	11,00	13	59	3,3	0,023	0,23	0,041	0,40
		50	230					3,1				
		50	240	MIN. 50Hz				3,0				

Symbols

① Hz	COMP Compressor
② Voltage	OFM Outdoor fan motor
③ Voltage range	IFM Indoor fan motor
MCA Minimum Circuit Ampere [A]	FLA Full Load Ampere [A]
MFA Maximum Fuse Ampere [A]	kW Fan motor rated output [kW]
RLA Rated load amps [A]	RHz Rated operating frequency [Hz]

Notes

- The ·RLA· is based on the following conditions.
Indoor temperature ·27·°C DB / ·19·°C WB
Outdoor temperature ·35·°C DB
- Select the wire size according to the MCA.
- The maximum allowable voltage that is unbalanced between phases is ·2·%.
- Use a circuit breaker instead of a fuse.