

Unit combination restrictions		Power supply				Compressor		OFM		IMF		
Indoor unit	Outdoor unit	Hz	Voltage	Voltage range	MCA	MFA	RLA	kW	FLA	kW	FLA	
FTXS20K3V1B	RXS20L3V1B	50	220 230 240	Maximum -50-Hz -264-V	8	10	2,30 2,20 2,10	0,023	0,24 0,23 0,22	0,016	0,19 0,18 0,17	
FTXS25K3V1B	RXS25L3V1B	50	220 230 240		8	10	2,82 2,70 2,59	0,023	0,24 0,23 0,22	0,016	0,19 0,18 0,17	
FVXS25FV1B	RXS25L3V1B	50	220 230 240		9,75	10	2,93 2,80 2,68	0,023	0,23	0,048	0,05	
FLXS25BAVMB	RXS25L3V1B	50	220 230 240		9,75	10	2,61 2,50 2,40	0,023	0,23	0,034	0,34	
FDXS25F2VEB	RXS25L3V1B	50	220 230 240		9,75	16	4,29 4,10 3,93	0,031	0,2	0,034	0,3	
FFQ25C2VEB	RXS25L3V1B	50	220 230 240		9,75	10	2,60 2,50 2,30	0,023	0,23	0,050	0,3	
ATXS25K3V1B	ARXS25L3V1B	50	220 230 240		8	10	2,82 2,70 2,59	0,023	0,24 0,23 0,22	0,016	0,19 0,18 0,17	
FFA25A2VEB9	RXS25L3V1B	50	220 230 240		Minimum -50-Hz -198-V	9,75	10	2,50	0,023	0,23	0,050	0,2
FDXM25F3V1B9	RXS25L3V1B	50	220 230 240			9,75	10	4,10	0,023	0,23	0,034	0,3
FNA25A2VEB9	RXS25L3V1B	50	220 230 240			9,75	10	4,10	0,023	0,23	0,034	0,3

### Notes

- The -RLA- is based on the following conditions.  
Indoor temperature :27°C DB / -19°C WB  
Outdoor temperature :35°C DB
- Select the wire size according to the MCA.
- The maximum allowable voltage that is unbalanced between phases is :2-%.
- Use a circuit breaker instead of a fuse.

### Symbols

- MCA Minimum Circuit Ampere [A]  
MFA Maximum Fuse Ampere [A]  
RLA Rated Load Amperes [A]  
OFM Outdoor fan motor  
IFM Indoor fan motor  
FLA Full Load Ampere [A]  
Kw Fan motor rated output [kW]