

RXS25-35L3

Unit combination restrictions		Power supply					COMP		OFM		IFM	
Indoor	Outdoor	①	②	③	MCA	MFA	RHz	RLA	kW	FLA	kW	FLA
FNQ25A2VEB	RXS25L3V1B	50	220– 240V	MAX. 50Hz 264V MIN. 50Hz 198V	12	16	54	4.1	0.031	0.2	0.034	0.3
FNQ35A2VEB	RXS35L3V1B						90	5.5	0.035	0.22		

Notes

- 1 The RLA is based on the following conditions.
Indoor temperature 27°C DB / 19°C WB
Outdoor temperature 35°C DB
- 2 Select the wire size according to the MCA.
- 3 The maximum allowable voltage that is unbalanced between phases is 2%.
- 4 Use a circuit breaker instead of a fuse.

Symbols

- ① Hz
 ② Voltage
 ③ Voltage range
- MCA Minimum Circuit Ampere (A)
 MFA Maximum Fuse Ampere (A)
 RLA Rated load amps [A]

- OFM Outdoor fan motor
 IFM Indoor fan motor
 FLA Full Load Ampere (A)
 kW Fan motor rated output [kW]
 RHz Rated operating frequency [Hz]
 COMP Compressor

3D096315C