

RXS35L3

| Unit combination restrictions | | Power supply | | | | | COMP | | OFM | | IFM | |
|-------------------------------|------------|--------------|----------|----------------------------------|-----|-----|------|-----|-------|------|-------|-----|
| Indoor | Outdoor | ① | ② | ③ | MCA | MFA | RHz | RLA | kW | FLA | kW | FLA |
| FBQ35D2VEB | RXS35L3V1B | 50 | 220-240V | MAX. 50Hz 264V MIN. 50Hz 198V | 15 | 16 | 63 | 3.1 | 0.023 | 0.23 | 0.089 | 0.6 |

Notes

- 1 The RLA is based on the following conditions.
Indoor temperature 27°C DB / 19°C WB
Outdoor temperature 35°C DB
- 2 Select the wire size according to the MCA.
- 3 The maximum allowable voltage that is unbalanced between phases is 2%.
- 4 Use a circuit breaker instead of a fuse.

Symbols

- ① Hz
- ② Voltage
- ③ Voltage range
- MCA Minimum Circuit Ampere (A)
- MFA Maximum Fuse Ampere (A)
- RLA Rated load amps [A]

- OFM Outdoor fan motor
- IFM Indoor fan motor
- FLA Full Load Ampere (A)
- kW Fan motor rated output [kW]
- RHz Rated operating frequency [Hz]
- COMP Compressor

3D094863B