

**RXS35L3**

Unit combination restrictions		Power supply					COMP		OFM		IFM	
Indoor unit	Outdoor unit	Hz	Voltage	Voltage range	MCA	MFA	RHz	RLA	kW	FLA	kW	FLA
FTXS35K3V1B	RXS35L3V1B	50	220	MAX. 50 Hz 264V MIN. 50Hz 198V	8,8	10	66	3,76	0,023	0,23	0,023	0,15
			230					3,60				
			240					3,45				
FVXS35FV1B	RXS35L3V1B	50	220	MAX. 50 Hz 264V MIN. 50Hz 198V	9,75	10	76	4,81	0,023	0,23	0,048	0,05
			230					4,60				
			240					4,41				
FLXS35BAVMB9	RXS35L3V1B	50	220	MAX. 50 Hz 264V MIN. 50Hz 198V	9,75	10	82	4,50	0,023	0,23	0,034	0,38
			230					4,30				
			240					4,12				
FDXS35F2VEB	RXS35L3V1B	50	220	MAX. 50 Hz 264V MIN. 50Hz 198V	9,75	16	78	5,75	0,035	0,22	0,034	0,3
			230					5,50				
			240					5,27				
FHQ35CBVEB	RXS35L3V1B	50	220	MAX. 50 Hz 264V MIN. 50Hz 198V	9,75	10	66	4,29	0,023	0,23	0,06	0,6
			230					4,10				
			240					3,93				
FBQ35C8VEB	RXS35L3V1B	50	220	MAX. 50 Hz 264V MIN. 50Hz 198V	9,75	16	80	4,62	0,019	0,35	0,14	1,2
			230					4,42				
			240					4,24				
FFQ35C2VEB	RXS35L3V1B	50	220	MAX. 50 Hz 264V MIN. 50Hz 198V	9,75	10		4,80	0,023	0,23	0,050	0,4
			230					4,60				
			240					4,40				
FCQG35FVEB	RXS35L3V1B	50	220	MAX. 50Hz 253V MIN. 50Hz 207V	9,75	10		7,10	0,023	0,23	0,048	0,3
			230					3,90				
			240					3,70				

Notes

- 1) The RLA is based on the following conditions.  
Indoor temperature 27°C DB / 19°C WB  
Outdoor temperature 35°C DB
- 2) Select the wire size according to the MCA.
- 3) The maximum allowable voltage that is unbalanced between phases is 2%.
- 4) Use a circuit breaker instead of a fuse.

Symbols

- MCA: Minimum Circuit Ampere [A]  
MFA: Maximum Fuse Ampere [A]  
RLA: Rated load amps [A]  
OFM: Outdoor fan motor  
IFM: Indoor fan motor  
FLA: Full Load Ampere [A]  
Kw: Fan motor rated output [kW]  
RHz: Rated operating frequency [Hz]