

# RXV-AB

Representative unit combination		Power supply					Comp.	OFM		IFM	
Indoor unit	Outdoor unit	Hz	Volts	Voltage range	MCA	MFA	RLA	W	RLA	W	RLA
FTXV25AV1B	RXV25AV1B	50	220-240	Max. 264Min. 198	7	10	4.9	30	0.15	20	0.1
FTXV35AV1B	RXV35AV1B	50	220-240		7	10	4.9	30	0.15	20	0.1
FTXV50AV1B	RXV50AV1B	50	220-240		11.8	25	7.2	60	0.37	20	0.31
FTXV60AV1B	RXV60AV1B	50	220-240		12.4	25	7.2	90	0.49	35	0.31

3D088626

## SYMBOLS

MCA	: Min. Circuit Amps. (A)
MFA	: Max. Fuse Amps (A)
RHz	: Rated operating frequency (Hz)
RLA	: Rated Load Amps. (A)
OFM	: Outdoor fan motors
IFM	: Indoor Fan Motor.
W	: Fan Motor Rated Output (W)

## NOTES

1. RLA is based on the following conditions:  
Indoor temp.: 27°CDB/19°CWB  
Outdoor temp.: 35°CDB
2. Maximum allowable voltage variation between phases is 2%.
3. Select wire size based on the larger value of MCA.
4. Instead of fuse, use circuit breaker.