
REYQ18,20P9
REYQ22-32P8

Model name			Units				Power supply			Compressor		OFM	
Combination unit	Independent unit		Hz	Volts	Min.	Max.	MCA	TOCA	MFA	MSC	RLA	KW	FLA
REYQ18P9	REMQ8P9	REMQ10P8	50	380	342	456	40.1	48.0	45	82	8.6 + 4.7 + 7.2	0.75 + 0.75	0.7 + 0.9
				400						78	8.2 + 4.5 + 6.8		
				415						75	7.9 + 4.3 + 6.6		
REYQ20P9	REMQ8P9	REMQ12P8	50	380	342	456	41.2	48.0	50	83	8.6 + 7.3 + 7.1	0.75 + 0.75	0.7 + 1.2
				400						79	8.2 + 7.0 + 6.7		
				415						76	7.9 + 6.7 + 6.5		
REYQ22P8	REMQ10P8	REMQ12P8	50	380	342	456	44.3	63.0	50	92	4.7 + 7.2 + 7.3 + 7.1	0.75 + 0.75	0.9 + 1.2
				400						88	4.5 + 6.8 + 7.0 + 6.7		
				415						84	4.3 + 6.6 + 6.7 + 6.5		
REYQ24P8	REMQ12P8	REMQ12P8	50	380	342	456	45.4	63.0	50	93	(7.3 + 7.1) x 2	0.75 + 0.75	1.2 + 1.2
				400						88	(7.0 + 6.7) x 2		
				415						85	(6.7 + 6.5) x 2		
REYQ26P8	REMQ10P8	REMQ16P8	50	380	342	456	53.1	77.9	60	103	4.7 + 7.2 + 6.4 + 8.0 x 2	0.75 + 0.35 x 2	0.9 + 0.6 x 2
				400						98	4.5 + 6.8 + 6.1 + 7.6 x 2		
				415						94	4.3 + 6.6 + 5.9 + 7.3 x 2		
REYQ28P8	REMQ12P8	REMQ16P8	50	380	342	456	54.2	77.9	60	103	7.3 + 7.1 + 6.4 + 8.0 x 2	0.75 + 0.35 x 2	1.2 + 0.6 x 2
				400						98	7.0 + 6.7 + 6.1 + 7.6 x 2		
				415						95	6.7 + 6.5 + 5.9 + 7.3 x 2		
REYQ30P8	REMQ14P8	REMQ16P8	50	380	342	456	63.0	92.8	70	113	3.6 + 7.9 x 2 + 6.4 + 8.0 x 2	(0.35 x 2) x 2	(0.6 x 2) x2
				400						108	3.4 + 7.5 x 2 + 6.1 + 7.6 x 2		
				415						104	3.3 + 7.3 x 2 + 5.9 + 7.3 x 2		
REYQ32P8	REMQ16P8	REMQ16P8	50	380	342	456	63.0	92.8	70	115	(6.4 + 8.0 x 2) x 2	(0.35 x 2) x 2	(0.6 x 2) x2
				400						109	(6.1 + 7.6 x 2) x 2		
				415						105	(5.9 + 7.3 x 2) x 2		

SYMBOLS

MCA : Min.Circuit Amps. (A)
TOCA : Total Over-current Amps. (A)
MFA : Max. Fuse Amps. (A)
MSC : Max. Starting current
RLA : Rated Load Amps. (A)
OFM : Outdoor Fan Motor
FLA : Full Load Amps. (A)
kW : Rated Motor Output (kW)



The relationship between the starting time and the starting current

NOTES

1. RLA is based on the following conditions:
   Indoor temp. 27°CDB/19.0°CWB
   Outdoor temp. 35°CDB
2. TOCA means the total value of each OC set.
3. MSC means the Max. current during the starting of compressor.
4. Voltage range:
   Units are suitable for use on electrical systems where voltage supplied to unit terminal is not below or above listed range limits.
5. Maximum allowable voltage variation between phases is 2%
6. Select wire size based on the larger value of MCA.
7. MFA is used to select the circuit breaker and the ground fault circuit interrupter (earth leakage circuit breaker).