

Combination (%)	Capacity index (kW)	Outdoor air temp.		Indoor air temperature: °CDB													
				16.0		18.0		20.0		21.0		22.0		24.0			
				TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI		
130%	650 (81.25 kW)	°CDB	°CWB														
		-19.8	-20.0	41.9	10.8	41.7	11.6	41.6	12.4	41.5	12.7	41.4	13.1	41.3	13.9		
		-18.8	-19.0	42.8	11.2	42.7	11.9	42.5	12.7	42.5	13.0	42.4	13.4	42.2	14.1		
		-16.7	-17.0	44.8	11.8	44.7	12.5	44.5	13.2	44.4	13.6	44.4	13.9	44.2	14.6		
		-13.7	-15.0	46.9	12.4	46.8	13.1	46.6	13.7	46.5	14.1	46.5	14.4	46.3	15.1		
		-11.8	-13.0	49.1	13.0	49.0	13.6	48.8	14.3	48.8	14.6	48.7	14.9	48.5	15.5		
		-9.8	-11.0	51.4	13.5	51.3	14.1	51.1	14.7	51.1	15.0	51.0	15.4	50.8	16.0		
		-9.5	-10.0	52.6	13.8	52.5	14.4	52.3	15.0	52.3	15.3	52.2	15.6	52.0	16.2		
		-8.5	-9.1	53.7	14.0	53.6	14.6	53.4	15.2	53.4	15.5	53.3	15.8	53.1	16.4		
		-7.0	-7.6	55.6	14.4	55.5	15.0	55.3	15.5	55.3	15.8	55.2	16.1	55.0	16.7		
		-5.0	-5.6	58.2	14.9	58.1	15.4	57.9	15.9	57.9	16.2	57.8	16.5	57.6	17.0		
		-3.0	-3.7	60.8	15.3	60.7	15.8	60.5	16.3	60.4	16.6	60.4	16.8	60.2	17.4		
		0.0	-0.7	65.1	15.9	65.0	16.4	64.8	16.9	64.7	17.1	64.7	17.4	64.5	17.9		
		3.0	2.2	69.5	16.5	69.3	17.0	69.2	17.4	69.1	17.6	69.0	17.9	68.9	18.3		
		5.0	4.1	72.5	16.9	72.3	17.3	72.2	17.7	72.1	17.9	72.0	18.2	70.8	18.2		
		7.0	6.0	75.6	17.2	75.4	17.6	75.3	18.0	75.2	18.2	75.1	18.4	70.8	17.2		
		9.0	7.9	78.7	17.5	78.6	17.9	78.4	18.3	78.4	18.5	78.3	18.7	70.8	16.4		
11.0	9.8	82.0	17.8	81.9	18.2	81.3	18.4	81.3	18.4	81.3	18.4	70.8	15.5				
13.0	11.8	85.6	18.1	85.4	18.5	85.3	18.5	85.3	18.5	85.3	18.5	70.8	14.8				
15.0	13.7	89.1	18.4	88.9	18.4	88.9	18.4	88.9	18.4	88.9	18.4	70.8	14.1				
120%	600 (75.00 kW)	-19.8	-20.0	41.7	11.9	41.5	12.6	41.4	13.3	41.3	13.6	41.3	14.0	41.1	14.7		
		-18.8	-19.0	42.6	12.2	42.5	12.9	42.4	13.5	42.3	13.9	42.2	14.2	42.1	14.9		
		-16.7	-17.0	44.6	12.7	44.5	13.4	44.3	14.1	44.3	14.4	44.2	14.7	44.1	15.4		
		-13.7	-15.0	46.7	13.3	46.6	13.9	46.4	14.6	46.4	14.9	46.3	15.2	46.2	15.8		
		-11.8	-13.0	48.9	13.8	48.8	14.4	48.6	15.0	48.6	15.3	48.5	15.6	48.4	16.2		
		-9.8	-11.0	51.2	14.3	51.1	14.9	51.0	15.5	50.9	15.8	50.8	16.0	50.7	16.6		
		-9.5	-10.0	52.4	14.6	52.3	15.1	52.2	15.7	52.1	16.0	52.0	16.2	51.9	16.8		
		-8.5	-9.1	53.5	14.8	53.4	15.3	53.3	15.9	53.2	16.2	53.1	16.4	53.0	17.0		
		-7.0	-7.6	55.4	15.1	55.3	15.7	55.1	16.2	55.1	16.5	55.0	16.7	54.9	17.2		
		-5.0	-5.6	58.0	15.6	57.9	16.1	57.8	16.6	57.7	16.8	57.6	17.1	57.5	17.6		
		-3.0	-3.7	60.6	16.0	60.5	16.5	60.3	17.0	60.3	17.2	60.2	17.4	60.1	17.9		
		0.0	-0.7	64.9	16.6	64.8	17.0	64.6	17.5	64.6	17.7	64.5	17.9	64.3	18.4		
		3.0	2.2	69.3	17.1	69.1	17.5	69.0	18.0	68.9	18.2	68.9	18.4	65.4	17.3		
		5.0	4.1	72.3	17.4	72.1	17.8	72.0	18.2	71.9	18.4	70.2	18.0	65.4	16.4		
		7.0	6.0	75.4	17.8	75.2	18.1	75.0	18.5	72.6	17.8	70.2	17.0	65.4	15.6		
		9.0	7.9	78.5	18.1	78.4	18.4	75.0	17.5	72.6	16.9	70.2	16.2	65.4	14.8		
		11.0	9.8	81.8	18.3	79.8	18.0	75.0	16.7	72.6	16.0	70.2	15.4	65.4	14.1		
13.0	11.8	84.6	18.3	79.8	17.1	75.0	15.8	72.6	15.2	70.2	14.6	65.4	13.4				
15.0	13.7	84.6	17.4	79.8	16.2	75.0	15.1	72.6	14.5	70.2	13.9	65.4	12.8				
110%	550 (68.75 kW)	-19.8	-20.0	41.5	12.9	41.4	13.5	41.2	14.2	41.2	14.5	41.1	14.8	41.0	15.5		
		-18.8	-19.0	42.4	13.2	42.3	13.8	42.2	14.4	42.1	14.7	42.1	15.1	41.9	15.7		
		-16.7	-17.0	44.4	13.7	44.3	14.3	44.2	14.9	44.1	15.2	44.0	15.5	43.9	16.1		
		-13.7	-15.0	46.5	14.2	46.4	14.8	46.3	15.4	46.2	15.6	46.1	15.9	46.0	16.5		
		-11.8	-13.0	48.7	14.7	48.6	15.3	48.5	15.8	48.4	16.1	48.3	16.3	48.2	16.9		
		-9.8	-11.0	51.0	15.2	50.9	15.7	50.8	16.2	50.7	16.5	50.7	16.7	50.5	17.3		
		-9.5	-10.0	52.2	15.4	52.1	15.9	52.0	16.4	51.9	16.7	51.9	16.9	51.7	17.4		
		-8.5	-9.1	53.3	15.6	53.2	16.1	53.1	16.6	53.0	16.8	53.0	17.1	52.8	17.6		
		-7.0	-7.6	55.2	15.9	55.1	16.4	55.0	16.9	54.9	17.1	54.8	17.4	54.7	17.8		
		-5.0	-5.6	57.8	16.3	57.7	16.8	57.6	17.2	57.5	17.5	57.5	17.7	57.3	18.2		
		-3.0	-3.7	60.4	16.7	60.3	17.1	60.2	17.6	60.1	17.8	60.0	18.0	59.9	18.4		
		0.0	-0.7	64.7	17.2	64.6	17.6	64.4	18.1	64.4	18.3	64.3	18.5	59.9	16.9		
		3.0	2.2	69.1	17.7	68.9	18.1	68.8	18.5	66.5	17.7	64.3	17.0	59.9	15.6		
		5.0	4.1	72.1	18.0	71.9	18.4	68.8	17.5	66.5	16.8	64.3	16.1	59.9	14.8		
		7.0	6.0	75.1	18.3	73.2	17.9	68.8	16.6	66.5	16.0	64.3	15.3	59.9	14.1		
		9.0	7.9	77.6	18.3	73.2	17.0	68.8	15.8	66.5	15.2	64.3	14.6	59.9	13.4		
		11.0	9.8	77.6	17.4	73.2	16.2	68.8	15.0	66.5	14.4	64.3	13.9	59.9	12.8		
13.0	11.8	77.6	16.5	73.2	15.4	68.8	14.3	66.5	13.7	64.3	13.2	59.9	12.1				
15.0	13.7	77.6	15.7	73.2	14.6	68.8	13.6	66.5	13.1	64.3	12.6	59.9	11.6				
100%	500 (62.50 kW)	-19.8	-20.0	41.3	13.9	41.2	14.5	41.0	15.1	41.0	15.4	40.9	15.7	40.8	16.3		
		-18.8	-19.0	42.2	14.2	42.1	14.8	42.0	15.3	41.9	15.6	41.9	15.9	41.8	16.5		
		-16.7	-17.0	44.2	14.7	44.1	15.2	44.0	15.8	43.9	16.0	43.9	16.3	43.8	16.8		
		-13.7	-15.0	46.3	15.1	46.2	15.7	46.1	16.2	46.0	16.4	46.0	16.7	45.9	17.2		
		-11.8	-13.0	48.5	15.6	48.4	16.1	48.3	16.6	48.2	16.8	48.2	17.1	48.1	17.6		
		-9.8	-11.0	50.8	16.0	50.7	16.5	50.6	16.9	50.5	17.2	50.5	17.4	50.4	17.9		
		-9.5	-10.0	52.0	16.2	51.9	16.7	51.8	17.1	51.7	17.4	51.7	17.6	51.6	18.1		
		-8.5	-9.1	53.1	16.4	53.0	16.8	52.9	17.3	52.8	17.5	52.8	17.7	52.7	18.2		
		-7.0	-7.6	55.0	16.7	54.9	17.1	54.8	17.6	54.7	17.8	54.7	18.0	54.5	18.4		
		-5.0	-5.6	57.6	17.1	57.5	17.5	57.4	17.9	57.3	18.1	57.3	18.3	54.5	17.3		
		-3.0	-3.7	60.2	17.4	60.1	17.8	60.0	18.2	59.9	18.4	58.5	17.9	54.5	16.4		
		0.0	-0.7	64.5	17.9	64.4	18.3	62.5	17.8	60.5	17.1	58.5	16.4	54.5	15.1		
		3.0	2.2	68.9	18.3	66.5	17.7	62.5	16.4	60.5	15.8	58.5	15.1	54.5	13.9		
		5.0	4.1	70.5	18.1	66.5	16.8	62.5	15.6	60.5	15.0	58.5	14.4	54.5	13.2		
		7.0	6.0	70.5	17.1	66.5	16.0	62.5	14.8	60.5	14.2	58.5	13.7	54.5	12.6		
		9.0	7.9	70.5	16.3	66.5	15.2	62.5	14.1	60.5	13.5	58.5	13.0	54.5	12.0		
		11.0	9.8	70.5	15.5	66.5	14.4	62.5	13.4	60.5	12.9	58.5	12.4	54.5	11.4		
13.0	11.8	70.5	14.7	66.5	13.7	62.5	12.7	60.5	12.3	58.5	11.8	54.5	10.9				
15.0	13.7	70.5	14.0	66.5	13.1	62.5	12.2	60.5	11.7	58.5	11.3	54.5	10.4				

NOTES

- █ is shown as reference.
When selecting the unit models, avoid the Outdoor air temperature range shown by █.
- The above table shows the average value of conditions which may occur.