

Combination (%)	Capacity index (kW)	Outdoor air temp.		Indoor air temperature: °CDB												
				16.0		18.0		20.0		21.0		22.0		24.0		
				TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	
130%	715 (89.70 kW)	°CDB	°CWB													
		-19.8	-20.0	46.2	12.2	46.0	13.1	45.9	13.9	45.8	14.4	45.7	14.8	45.5	15.7	
		-18.8	-19.0	47.0	12.5	46.9	13.4	46.7	14.2	46.6	14.6	46.5	15.0	46.4	15.9	
		-16.7	-17.0	48.8	13.1	48.7	13.9	48.5	14.7	48.4	15.1	48.3	15.5	48.2	16.3	
		-13.7	-15.0	50.8	13.7	50.7	14.5	50.5	15.2	50.4	15.6	50.3	16.0	50.2	16.8	
		-11.8	-13.0	53.0	14.3	52.9	15.0	52.7	15.8	52.6	16.1	52.5	16.5	52.4	17.3	
		-9.8	-11.0	55.5	14.9	55.3	15.6	55.1	16.3	55.0	16.7	55.0	17.0	54.8	17.7	
		-9.5	-10.0	56.8	15.2	56.6	15.9	56.4	16.6	56.3	16.9	56.3	17.3	56.1	18.0	
		-8.5	-9.1	58.0	15.5	57.8	16.1	57.6	16.8	57.6	17.2	57.5	17.5	57.3	18.2	
		-7.0	-7.6	60.1	15.9	59.9	16.6	59.7	17.2	59.7	17.5	59.6	17.9	59.4	18.5	
		-5.0	-5.6	63.1	16.5	62.9	17.1	62.7	17.7	62.7	18.0	62.6	18.3	62.4	18.9	
		-3.0	-3.7	66.1	17.0	66.0	17.6	65.8	18.2	65.7	18.5	65.6	18.8	65.5	19.4	
		0.0	-0.7	71.3	17.8	71.2	18.3	71.0	18.9	70.9	19.2	70.8	19.4	70.7	20.0	
		3.0	2.2	76.8	18.5	76.6	19.0	76.5	19.5	76.4	19.8	76.3	20.0	76.1	20.5	
		5.0	4.1	80.6	19.0	80.5	19.4	80.3	19.9	80.2	20.1	80.1	20.4	79.9	20.9	
		7.0	6.0	84.7	19.4	84.5	19.8	84.3	20.3	84.2	20.5	84.1	20.6	83.9	21.1	
		9.0	7.9	88.9	19.8	88.7	20.2	88.6	20.6	88.5	20.8	88.4	21.0	88.3	21.5	
11.0	9.8	93.3	20.1	93.1	20.6	92.9	20.9	92.8	21.1	92.7	21.3	92.6	21.8			
13.0	11.8	98.1	20.5	97.9	21.0	97.7	21.3	97.6	21.5	97.5	21.7	97.4	22.1			
15.0	13.7	101	20.3	95.5	18.9	89.7	17.5	86.8	16.8	83.9	16.1	78.2	14.8			
120%	660 (82.80 kW)	-19.8	-20.0	46.0	13.4	45.8	14.2	45.7	15.0	45.6	15.4	45.5	15.8	45.4	16.6	
		-18.8	-19.0	46.8	13.7	46.7	14.4	46.5	15.2	46.4	15.6	46.3	16.0	46.2	16.8	
		-16.7	-17.0	48.6	14.2	48.4	14.9	48.3	15.7	48.2	16.1	48.1	16.4	48.0	17.2	
		-13.7	-15.0	50.6	14.7	50.4	15.5	50.3	16.2	50.2	16.5	50.1	16.9	50.0	17.6	
		-11.8	-13.0	52.8	15.3	52.7	16.0	52.5	16.7	52.4	17.0	52.4	17.3	52.2	18.0	
		-9.8	-11.0	55.2	15.9	55.1	16.5	54.9	17.2	54.9	17.5	54.8	17.8	54.6	18.5	
		-9.5	-10.0	56.5	16.1	56.4	16.8	56.2	17.4	56.1	17.7	56.1	18.0	55.9	18.7	
		-8.5	-9.1	57.7	16.4	57.6	17.0	57.4	17.6	57.4	17.9	57.3	18.2	57.1	18.9	
		-7.0	-7.6	59.9	16.8	59.7	17.4	59.5	18.0	59.5	18.3	59.4	18.6	59.2	19.2	
		-5.0	-5.6	62.9	17.3	62.7	17.9	62.5	18.5	62.5	18.7	62.4	19.0	62.2	19.6	
		-3.0	-3.7	65.9	17.8	65.7	18.3	65.6	18.9	65.5	19.2	65.4	19.4	65.3	20.0	
		0.0	-0.7	71.1	18.5	70.9	19.0	70.8	19.5	70.7	19.8	70.6	20.0	70.5	20.5	
		3.0	2.2	76.6	19.2	76.4	19.7	76.3	20.1	76.2	20.4	76.1	20.6	76.0	21.1	
		5.0	4.1	80.4	19.6	80.3	20.0	80.1	20.5	80.0	20.7	79.9	20.9	79.8	21.4	
		7.0	6.0	84.4	20.0	84.3	20.4	84.2	20.8	84.1	21.1	84.0	21.3	83.9	21.8	
		9.0	7.9	88.7	20.4	88.1	20.6	87.8	21.0	87.7	21.3	87.6	21.5	87.5	22.0	
		11.0	9.8	93.1	20.7	92.8	21.0	92.7	21.3	92.6	21.5	92.5	21.7	92.4	22.2	
13.0	11.8	93.4	19.5	88.1	18.2	82.8	16.8	80.1	16.2	77.5	15.6	72.2	14.3			
15.0	13.7	93.4	18.4	88.1	17.1	82.8	15.9	80.1	15.3	77.5	14.7	72.2	13.5			
110%	605 (75.90 kW)	-19.8	-20.0	45.8	14.6	45.6	15.3	45.5	16.0	45.4	16.4	45.3	16.7	45.2	17.4	
		-18.8	-19.0	46.6	14.8	46.4	15.5	46.3	16.2	46.2	16.6	46.2	16.9	46.0	17.6	
		-16.7	-17.0	48.4	15.3	48.2	16.0	48.1	16.6	48.0	17.0	47.9	17.3	47.8	18.0	
		-13.7	-15.0	50.4	15.8	50.2	16.4	50.1	17.1	50.0	17.4	50.0	17.7	49.8	18.4	
		-11.8	-13.0	52.6	16.3	52.4	16.9	52.3	17.5	52.2	17.9	52.2	18.2	52.0	18.8	
		-9.8	-11.0	55.0	16.8	54.9	17.4	54.7	18.0	54.7	18.3	54.6	18.6	54.5	19.2	
		-9.5	-10.0	56.3	17.1	56.2	17.6	56.0	18.2	56.0	18.5	55.9	18.8	55.7	19.4	
		-8.5	-9.1	57.5	17.3	57.4	17.9	57.2	18.4	57.2	18.7	57.1	19.0	57.0	19.6	
		-7.0	-7.6	59.6	17.7	59.5	18.2	59.3	18.8	59.3	19.0	59.2	19.3	59.1	19.9	
		-5.0	-5.6	62.6	18.1	62.5	18.7	62.3	19.2	62.3	19.5	62.2	19.7	62.1	20.2	
		-3.0	-3.7	65.7	18.6	65.5	19.1	65.4	19.6	65.3	19.8	65.3	20.1	65.1	20.6	
		0.0	-0.7	70.9	19.3	70.7	19.7	70.6	20.2	70.5	20.4	70.5	20.6	70.4	21.1	
		3.0	2.2	76.4	19.9	76.2	20.3	76.1	20.6	76.0	20.8	75.9	21.0	75.8	21.5	
		5.0	4.1	80.2	20.2	80.1	20.6	79.9	21.0	79.8	21.3	79.7	21.5	79.6	22.0	
		7.0	6.0	84.2	20.6	84.0	21.0	83.8	21.4	83.7	21.7	83.6	21.9	83.5	22.4	
		9.0	7.9	88.7	20.9	88.5	21.3	88.3	21.7	88.2	22.0	88.1	22.2	88.0	22.7	
		11.0	9.8	93.7	21.3	93.5	21.7	93.4	22.0	93.3	22.2	93.2	22.4	93.1	22.9	
13.0	11.8	93.7	17.5	88.8	16.3	83.9	15.2	79.0	14.6	74.1	14.1	69.2	13.5			
15.0	13.7	93.7	16.5	88.8	15.4	83.9	14.3	79.0	13.8	74.1	13.3	69.2	12.3			
100%	550 (69.00 kW)	-19.8	-20.0	45.5	15.7	45.4	16.4	45.3	17.0	45.2	17.4	45.2	17.7	45.0	18.3	
		-18.8	-19.0	46.4	15.9	46.2	16.6	46.1	17.2	46.0	17.5	46.0	17.9	45.8	18.5	
		-16.7	-17.0	48.1	16.4	48.0	17.0	47.9	17.6	47.8	17.9	47.8	18.2	47.6	18.9	
		-13.7	-15.0	50.1	16.8	50.0	17.4	49.9	18.0	49.8	18.3	49.8	18.6	49.6	19.2	
		-11.8	-13.0	52.4	17.3	52.2	17.9	52.1	18.4	52.0	18.7	52.0	19.0	51.9	19.6	
		-9.8	-11.0	54.8	17.8	54.7	18.3	54.5	18.8	54.5	19.1	54.4	19.4	54.3	19.9	
		-9.5	-10.0	56.1	18.0	56.0	18.5	55.8	19.1	55.8	19.3	55.7	19.6	55.6	20.1	
		-8.5	-9.1	57.3	18.2	57.2	18.7	57.0	19.2	57.0	19.5	56.9	19.8	56.8	20.3	
		-7.0	-7.6	59.4	18.5	59.3	19.0	59.1	19.5	59.1	19.8	59.0	20.0	58.9	20.5	
		-5.0	-5.6	62.4	19.0	62.3	19.5	62.2	19.9	62.1	20.2	62.0	20.4	61.9	19.9	
		-3.0	-3.7	65.5	19.4	65.3	19.8	65.2	20.3	65.1	20.5	64.6	20.5	64.1	18.8	
		0.0	-0.7	70.7	20.0	70.5	20.4	70.4	20.8	70.3	21.1	70.2	21.3	70.1	21.8	
		3.0	2.2	76.1	20.6	75.9	21.0	75.8	21.4	75.7	21.7	75.6	21.9	75.5	22.4	
		5.0	4.1	77.9	20.0	73.4	18.6	69.0	17.3	66.8	16.6	64.6	15.9	60.1	14.6	
		7.0	6.0	77.9	18.8	73.4	17.5	69.0	16.2	66.8	15.6	64.6	15.0	60.1	13.8	
		9.0	7.9	77.9	17.7	73.4	16.5	69.0	15.3	66.8	14.7	64.6	14.2	60.1	13.0	
		11.0	9.8	77.9	16.7	73.4	15.5	69.0	14.4	66.8	13.9	64.6	13.4	60.1	12.3	
13.0	11.8	77.9	15.7	73.4	14.6	69.0	13.6	66.8	13.1	64.6	12.6	60.1	11.6			
15.0	13.7	77.9	14.8	73.4	13.8	69.0	12.8	66.8	12.4	64.6	11.9	60.1	11.0			

NOTES

- █ is shown as reference. When selecting the unit models, avoid the Outdoor air temperature range shown by █.
- The above table shows the average value of conditions which may occur.