

Combination (%)	Capacity index (kW)	Outdoor air temp.		Indoor air temperature: °CDB												
				16.0		18.0		20.0		21.0		22.0		24.0		
				TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	
130%	780 (97.50 kW)	°CDB	°CWB													
		-19.8	-20.0	49.2	12.6	49.0	13.5	48.8	14.5	48.7	14.9	48.6	15.4	48.5	16.4	
		-18.8	-19.0	50.2	13.0	50.1	13.9	49.9	14.8	49.8	15.3	49.7	15.7	49.5	16.6	
		-16.7	-17.0	52.5	13.7	52.3	14.6	52.2	15.5	52.1	15.9	52.0	16.3	51.8	17.2	
		-13.7	-15.0	54.9	14.4	54.7	15.3	54.6	16.1	54.5	16.5	54.4	16.9	54.2	17.8	
		-11.8	-13.0	57.5	15.1	57.3	15.9	57.1	16.7	57.0	17.1	56.9	17.5	56.7	18.3	
		-9.8	-11.0	60.2	15.8	60.0	16.6	59.8	17.3	59.7	17.7	59.6	18.1	59.4	18.8	
		-9.5	-10.0	61.6	16.1	61.4	16.9	61.2	17.6	61.1	18.0	61.0	18.3	60.8	19.1	
		-8.5	-9.1	62.8	16.4	62.7	17.1	62.5	17.9	62.4	18.2	62.3	18.6	62.1	19.3	
		-7.0	-7.6	65.1	16.9	64.9	17.6	64.7	18.3	64.6	18.6	64.5	19.0	64.3	19.7	
		-5.0	-5.6	68.1	17.4	68.0	18.1	67.8	18.8	67.7	19.1	67.6	19.5	67.4	20.1	
		-3.0	-3.7	71.2	18.0	71.0	18.6	70.8	19.3	70.8	19.6	70.7	19.9	70.5	20.5	
		0.0	-0.7	76.3	18.8	76.1	19.4	75.9	20.0	75.8	20.3	75.8	20.5	75.6	21.1	
		3.0	2.2	81.5	19.5	81.3	20.0	81.2	20.6	81.1	20.9	81.0	21.1	80.8	21.7	
		5.0	4.1	85.1	19.9	84.9	20.4	84.8	21.0	84.7	21.2	84.6	21.5	84.4	22.0	
		7.0	6.0	88.8	20.3	88.6	20.8	88.5	21.3	88.4	21.6	88.3	21.8	88.0	21.1	
		9.0	7.9	92.7	20.7	92.5	21.2	92.3	21.7	92.2	21.9	91.2	21.8	85.0	20.0	
11.0	9.8	96.7	21.1	96.5	21.5	96.3	22.0	94.4	21.6	91.2	20.7	85.0	19.0			
13.0	11.8	101	21.4	101	21.9	97.5	21.2	94.4	20.4	91.2	19.6	85.0	18.0			
15.0	13.7	105	21.8	104	21.8	97.5	20.2	94.4	19.4	91.2	18.6	85.0	17.1			
120%	720 (90.00 kW)	-19.8	-20.0	48.9	13.9	48.8	14.7	48.6	15.6	48.5	16.0	48.4	16.5	48.3	17.3	
		-18.8	-19.0	50.0	14.2	49.8	15.1	49.7	15.9	49.6	16.3	49.5	16.8	49.3	17.6	
		-16.7	-17.0	52.3	14.9	52.1	15.7	51.9	16.5	51.9	16.9	51.8	17.3	51.6	18.1	
		-13.7	-15.0	54.7	15.6	54.5	16.3	54.3	17.1	54.3	17.5	54.2	17.9	54.0	18.7	
		-11.8	-13.0	57.2	16.2	57.1	16.9	56.9	17.7	56.8	18.0	56.7	18.4	56.6	19.2	
		-9.8	-11.0	59.9	16.8	59.7	17.5	59.6	18.2	59.5	18.6	59.4	18.9	59.3	19.6	
		-9.5	-10.0	61.3	17.1	61.1	17.8	61.0	18.5	60.9	18.8	60.8	19.2	60.7	19.9	
		-8.5	-9.1	62.6	17.4	62.4	18.1	62.3	18.7	62.2	19.1	62.1	19.4	61.9	20.1	
		-7.0	-7.6	64.8	17.8	64.7	18.5	64.5	19.1	64.4	19.4	64.3	19.7	64.2	20.4	
		-5.0	-5.6	67.9	18.4	67.7	19.0	67.6	19.6	67.5	19.9	67.4	20.2	67.2	20.8	
		-3.0	-3.7	71.0	18.8	70.8	19.4	70.6	20.0	70.5	20.3	70.5	20.6	70.3	21.2	
		0.0	-0.7	76.0	19.6	75.9	20.1	75.7	20.7	75.6	20.9	75.6	21.2	75.4	21.8	
		3.0	2.2	81.3	20.2	81.1	20.7	80.9	21.2	80.9	21.5	80.8	21.8	80.4	21.3	
		5.0	4.1	84.9	20.6	84.7	21.1	84.5	21.6	84.5	21.8	84.2	22.0	78.4	20.2	
		7.0	6.0	88.6	21.0	88.4	21.5	88.3	21.9	87.1	21.7	84.2	20.9	78.4	19.1	
		9.0	7.9	92.4	21.4	92.3	21.8	90.0	21.4	87.1	20.6	84.2	19.8	78.4	18.1	
		11.0	9.8	96.4	21.7	95.8	22.0	90.0	20.3	87.1	19.5	84.2	18.8	78.4	17.0	
13.0	11.8	101	22.0	95.8	20.8	90.0	19.2	87.1	18.5	84.2	17.8	78.4	16.3			
15.0	13.7	102	21.2	95.8	19.7	90.0	18.3	87.1	17.6	84.2	16.9	78.4	15.6			
110%	660 (82.50 kW)	-19.8	-20.0	48.7	15.1	48.5	15.9	48.4	16.7	48.3	17.1	48.2	17.5	48.1	18.3	
		-18.8	-19.0	49.8	15.5	49.6	16.2	49.5	17.0	49.4	17.4	49.3	17.8	49.2	18.6	
		-16.7	-17.0	52.0	16.1	51.9	16.8	51.7	17.6	51.6	17.9	51.6	18.3	51.4	19.1	
		-13.7	-15.0	54.4	16.7	54.3	17.4	54.1	18.1	54.0	18.5	54.0	18.8	53.8	19.5	
		-11.8	-13.0	57.0	17.3	56.8	18.0	56.7	18.6	56.6	19.0	56.5	19.3	56.4	20.0	
		-9.8	-11.0	59.7	17.9	59.5	18.5	59.4	19.1	59.3	19.5	59.2	19.8	59.1	20.4	
		-9.5	-10.0	61.1	18.1	60.9	18.8	60.8	19.4	60.7	19.7	60.6	20.0	60.5	20.6	
		-8.5	-9.1	62.4	18.4	62.2	19.0	62.1	19.6	62.0	19.9	61.9	20.2	61.8	20.8	
		-7.0	-7.6	64.6	18.8	64.4	19.3	64.3	19.9	64.2	20.2	64.1	20.5	64.0	21.1	
		-5.0	-5.6	67.7	19.3	67.5	19.8	67.4	20.4	67.3	20.7	67.2	20.9	67.0	21.5	
		-3.0	-3.7	70.7	19.7	70.6	20.2	70.4	20.8	70.3	21.1	70.3	21.3	70.1	21.9	
		0.0	-0.7	75.8	20.4	75.7	20.9	75.5	21.4	75.4	21.6	75.3	21.9	71.9	20.8	
		3.0	2.2	81.0	21.0	80.9	21.4	80.7	21.9	79.9	21.8	77.2	20.9	71.9	19.2	
		5.0	4.1	84.6	21.3	84.5	21.8	82.5	21.5	79.9	20.6	77.2	19.8	71.9	18.2	
		7.0	6.0	88.3	21.7	87.8	22.0	82.5	20.3	79.9	19.5	77.2	18.8	71.9	17.2	
		9.0	7.9	92.2	22.0	87.8	20.8	82.5	19.3	79.9	18.5	77.2	17.8	71.9	16.4	
		11.0	9.8	93.1	21.2	87.8	19.7	82.5	18.3	79.9	17.6	77.2	16.9	71.9	15.6	
13.0	11.8	93.1	20.1	87.8	18.7	82.5	17.3	79.9	16.7	77.2	16.0	71.9	14.8			
15.0	13.7	93.1	19.1	87.8	17.8	82.5	16.5	79.9	15.9	77.2	15.3	71.9	14.1			
100%	600 (75.00 kW)	-19.8	-20.0	48.4	16.4	48.3	17.1	48.2	17.9	48.1	18.2	48.0	18.6	47.9	19.3	
		-18.8	-19.0	49.5	16.7	49.4	17.4	49.2	18.1	49.2	18.5	49.1	18.8	49.0	19.5	
		-16.7	-17.0	51.8	17.3	51.6	17.9	51.5	18.6	51.4	19.0	51.4	19.3	51.2	20.0	
		-13.7	-15.0	54.2	17.8	54.0	18.5	53.9	19.1	53.8	19.4	53.8	19.8	53.6	20.4	
		-11.8	-13.0	56.7	18.4	56.6	19.0	56.5	19.6	56.4	19.9	56.3	20.2	56.2	20.8	
		-9.8	-11.0	59.4	18.9	59.3	19.5	59.2	20.1	59.1	20.3	59.0	20.6	58.9	21.2	
		-9.5	-10.0	60.8	19.1	60.7	19.7	60.6	20.3	60.5	20.6	60.4	20.8	60.3	21.4	
		-8.5	-9.1	62.1	19.3	62.0	19.9	61.8	20.5	61.8	20.7	61.7	21.0	61.6	21.6	
		-7.0	-7.6	64.3	19.7	64.2	20.2	64.1	20.8	64.0	21.1	63.9	21.3	63.8	21.9	
		-5.0	-5.6	67.4	20.2	67.3	20.7	67.1	21.2	67.1	21.4	67.0	21.7	65.4	21.4	
		-3.0	-3.7	70.5	20.6	70.3	21.1	70.2	21.5	70.1	21.8	70.1	22.0	65.4	20.2	
		0.0	-0.7	75.6	21.2	75.4	21.6	75.0	22.0	72.6	21.1	70.2	20.2	65.4	18.6	
		3.0	2.2	80.8	21.7	79.8	21.8	75.0	20.2	72.6	19.4	70.2	18.6	65.4	17.1	
		5.0	4.1	84.4	22.1	79.8	20.6	75.0	19.1	72.6	18.4	70.2	17.6	65.4	16.2	
		7.0	6.0	84.6	21.0	79.8	19.5	75.0	18.1	72.6	17.4	70.2	16.7	65.4	15.4	
		9.0	7.9	84.6	19.9	79.8	18.5	75.0	17.2	72.6	16.6	70.2	15.9	65.4	14.7	
		11.0	9.8	84.6	18.9	79.8	17.6	75.0	16.3	72.6	15.7	70.2	15.1	65.4	14.0	
13.0	11.8	84.6	17.9	79.8	16.7	75.0	15.5	72.6	14.9	70.2	14.4	65.4	13.3			
15.0	13.7	84.6	17.0	79.8	15.9	75.0	14.8	72.6	14.2	70.2	13.7	65.4	12.7			

**NOTES**

- █ is shown as reference.  
When selecting the unit models, avoid the Outdoor air temperature range shown by █.
- The above table shows the average value of conditions which may occur.