

Combination (%)	Capacity index (kW)	Outdoor air temp.		Indoor air temperature: °CDB											
				16.0		18.0		20.0		21.0		22.0		24.0	
				TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
130%	845 (105.95 kW)	-19.8	-20.0	50.0	10.5	49.8	11.5	49.6	12.5	49.5	13.0	49.4	13.4	49.2	14.4
		-18.8	-19.0	51.0	10.9	50.8	11.9	50.6	12.8	50.5	13.3	50.4	13.8	50.2	14.7
		-16.7	-17.0	53.3	11.7	53.1	12.6	52.9	13.5	52.8	13.9	52.7	14.4	52.5	15.3
		-13.7	-15.0	55.7	12.4	55.5	13.3	55.3	14.1	55.2	14.6	55.1	15.0	54.9	15.9
		-11.8	-13.0	58.3	13.1	58.1	14.0	57.9	14.8	57.8	15.2	57.7	15.6	57.5	16.4
		-9.8	-11.0	61.0	13.8	60.8	14.6	60.6	15.4	60.5	15.8	60.4	16.2	60.2	17.0
		-9.5	-10.0	62.4	14.2	62.2	14.9	62.0	15.7	61.9	16.1	61.8	16.5	61.6	17.2
		-8.5	-9.1	63.7	14.4	63.5	15.2	63.3	15.9	63.2	16.3	63.1	16.7	62.9	17.4
		-7.0	-7.6	65.9	14.9	65.7	15.6	65.5	16.4	65.4	16.7	65.3	17.1	65.1	17.8
		-5.0	-5.6	69.1	15.5	68.9	16.2	68.7	16.9	68.6	17.3	68.5	17.6	68.3	18.3
		-3.0	-3.7	72.2	16.1	72.0	16.7	71.8	17.4	71.7	17.7	71.6	18.1	71.4	18.7
		0.0	-0.7	77.3	16.9	77.1	17.5	76.9	18.1	76.8	18.4	76.7	18.7	76.6	19.3
		3.0	2.2	82.7	17.6	82.5	18.2	82.3	18.8	82.2	19.1	82.1	19.3	81.9	19.9
		5.0	4.1	86.3	18.1	86.1	18.6	85.9	19.2	85.8	19.4	85.7	19.7	85.5	20.3
		7.0	6.0	90.1	18.5	89.9	19.0	89.7	19.5	89.6	19.8	89.5	20.1	89.3	20.6
		9.0	7.9	94.1	18.9	93.9	19.4	93.7	19.9	93.6	20.2	93.5	20.4	92.3	20.6
		11.0	9.8	98.1	19.3	97.9	19.8	97.7	20.2	97.6	20.5	97.5	20.7	92.3	19.5
13.0	11.8	103	19.7	102	20.1	102	20.6	102	20.8	99.1	20.1	92.3	18.5		
15.0	13.7	107	20.0	107	20.4	106	20.7	103	19.9	99.1	19.1	92.3	17.6		
120%	780 (97.80 kW)	-19.8	-20.0	49.7	11.8	49.5	12.7	49.3	13.6	49.2	14.1	49.1	14.5	49.0	15.4
		-18.8	-19.0	50.8	12.2	50.6	13.1	50.4	14.0	50.3	14.4	50.2	14.8	50.0	15.7
		-16.7	-17.0	53.0	12.9	52.8	13.7	52.7	14.6	52.6	15.0	52.5	15.4	52.3	16.3
		-13.7	-15.0	55.4	13.6	55.3	14.4	55.1	15.2	55.0	15.6	54.9	16.0	54.7	16.8
		-11.8	-13.0	58.0	14.2	57.8	15.0	57.6	15.8	57.5	16.1	57.5	16.5	57.3	17.3
		-9.8	-11.0	60.7	14.9	60.5	15.6	60.3	16.3	60.3	16.7	60.2	17.1	60.0	17.8
		-9.5	-10.0	62.1	15.2	61.9	15.9	61.8	16.6	61.7	17.0	61.6	17.3	61.4	18.0
		-8.5	-9.1	63.4	15.5	63.2	16.2	63.1	16.8	63.0	17.2	62.9	17.5	62.7	18.2
		-7.0	-7.6	65.7	15.9	65.5	16.6	65.3	17.2	65.2	17.6	65.1	17.9	64.9	18.6
		-5.0	-5.6	68.8	16.5	68.6	17.1	68.4	17.7	68.3	18.1	68.2	18.4	68.1	19.0
		-3.0	-3.7	71.9	17.0	71.7	17.6	71.5	18.2	71.4	18.5	71.3	18.8	71.2	19.4
		0.0	-0.7	77.1	17.7	76.9	18.3	76.7	18.9	76.6	19.1	76.5	19.4	76.3	20.0
		3.0	2.2	82.4	18.4	82.2	18.9	82.0	19.5	81.9	19.7	81.9	20.0	81.7	20.5
		5.0	4.1	86.1	18.8	85.9	19.3	85.7	19.8	85.6	20.1	85.5	20.3	85.2	20.8
		7.0	6.0	89.9	19.2	89.7	19.7	89.5	20.2	89.4	20.4	89.3	20.7	85.2	19.7
		9.0	7.9	93.8	19.6	93.6	20.0	93.4	20.5	93.3	20.7	91.5	20.3	85.2	18.7
		11.0	9.8	97.9	19.9	97.7	20.4	97.5	20.8	94.7	20.1	91.5	19.3	85.2	17.7
13.0	11.8	102	20.3	102	20.7	97.8	19.8	94.7	19.0	91.5	18.3	85.2	16.8		
15.0	13.7	107	20.6	104	20.3	97.8	18.8	94.7	18.1	91.5	17.4	85.2	16.0		
110%	715 (89.65 kW)	-19.8	-20.0	49.4	13.2	49.3	14.0	49.1	14.8	49.0	15.2	48.9	15.6	48.8	16.4
		-18.8	-19.0	50.5	13.5	50.3	14.3	50.2	15.1	50.1	15.5	50.0	15.9	49.8	16.7
		-16.7	-17.0	52.8	14.1	52.6	14.9	52.4	15.7	52.3	16.0	52.3	16.4	52.1	17.2
		-13.7	-15.0	55.2	14.8	55.0	15.5	54.8	16.2	54.8	16.6	54.7	17.0	54.5	17.7
		-11.8	-13.0	57.7	15.4	57.6	16.1	57.4	16.8	57.3	17.1	57.2	17.5	57.1	18.2
		-9.8	-11.0	60.4	15.9	60.3	16.6	60.1	17.3	60.0	17.6	59.9	17.9	59.8	18.6
		-9.5	-10.0	61.9	16.2	61.7	16.9	61.5	17.5	61.4	17.8	61.4	18.2	61.2	18.8
		-8.5	-9.1	63.2	16.5	63.0	17.1	62.8	17.7	62.7	18.1	62.7	18.4	62.5	19.0
		-7.0	-7.6	65.4	16.9	65.2	17.5	65.1	18.1	65.0	18.4	64.9	18.7	64.7	19.3
		-5.0	-5.6	68.5	17.4	68.4	18.0	68.2	18.6	68.1	18.8	68.0	19.1	67.9	19.7
		-3.0	-3.7	71.6	17.9	71.5	18.4	71.3	19.0	71.2	19.3	71.1	19.5	71.0	20.1
		0.0	-0.7	76.8	18.6	76.6	19.1	76.5	19.6	76.4	19.8	76.3	20.1	76.1	20.6
		3.0	2.2	82.1	19.2	82.0	19.7	81.8	20.1	81.7	20.4	81.6	20.6	81.1	19.8
		5.0	4.1	85.8	19.5	85.6	20.0	85.5	20.5	85.4	20.7	83.9	20.4	78.1	18.7
		7.0	6.0	89.6	19.9	89.4	20.4	89.3	20.8	86.8	20.1	83.9	19.3	78.1	17.7
		9.0	7.9	93.5	20.3	93.4	20.7	89.7	19.8	86.8	19.1	83.9	18.3	78.1	16.8
		11.0	9.8	97.6	20.6	95.4	20.3	89.7	18.8	86.8	18.1	83.9	17.4	78.1	16.0
13.0	11.8	101	20.6	95.4	19.2	89.7	17.8	86.8	17.2	83.9	16.5	78.1	15.2		
15.0	13.7	101	19.6	95.4	18.2	89.7	17.0	86.8	16.3	83.9	15.7	78.1	14.5		
100%	650 (81.50 kW)	-19.8	-20.0	49.2	14.5	49.0	15.2	48.9	16.0	48.8	16.3	48.7	16.7	48.6	17.5
		-18.8	-19.0	50.2	14.8	50.1	15.5	49.9	16.2	49.9	16.6	49.8	17.0	49.6	17.7
		-16.7	-17.0	52.5	15.4	52.3	16.1	52.2	16.7	52.1	17.1	52.0	17.4	51.9	18.1
		-13.7	-15.0	54.9	15.9	54.8	16.6	54.6	17.3	54.5	17.6	54.5	17.9	54.3	18.6
		-11.8	-13.0	57.5	16.5	57.3	17.1	57.2	17.7	57.1	18.1	57.0	18.4	56.9	19.0
		-9.8	-11.0	60.2	17.0	60.0	17.6	59.9	18.2	59.8	18.5	59.7	18.8	59.6	19.4
		-9.5	-10.0	61.6	17.3	61.4	17.8	61.3	18.4	61.2	18.7	61.1	19.0	61.0	19.6
		-8.5	-9.1	62.9	17.5	62.7	18.1	62.6	18.6	62.5	18.9	62.4	19.2	62.3	19.8
		-7.0	-7.6	65.1	17.9	65.0	18.4	64.8	19.0	64.8	19.2	64.7	19.5	64.5	20.1
		-5.0	-5.6	68.3	18.3	68.1	18.9	68.0	19.4	67.9	19.6	67.8	19.9	67.7	20.4
		-3.0	-3.7	71.4	18.7	71.2	19.3	71.1	19.8	71.0	20.0	70.9	20.3	70.8	20.8
		0.0	-0.7	76.5	19.4	76.4	19.8	76.2	20.3	76.2	20.6	76.1	20.8	71.0	19.1
		3.0	2.2	81.9	19.9	81.7	20.4	81.5	20.8	78.9	20.0	76.3	19.2	71.0	17.6
		5.0	4.1	85.5	20.3	85.4	20.7	81.5	19.7	78.9	18.9	76.3	18.2	71.0	16.7
		7.0	6.0	89.3	20.6	86.7	20.1	81.5	18.7	78.9	17.9	76.3	17.2	71.0	15.9
		9.0	7.9	92.0	20.5	86.7	19.1	81.5	17.7	78.9	17.0	76.3	16.4	71.0	15.1
		11.0	9.8	92.0	19.4	86.7	18.1	81.5	16.8	78.9	16.2	76.3	15.6	71.0	14.4
13.0	11.8	92.0	18.4	86.7	17.2	81.5	16.0	78.9	15.4	76.3	14.8	71.0	13.6		
15.0	13.7	92.0	17.5	86.7	16.3	81.5	15.2	78.9	14.6	76.3	14.1	71.0	13.0		

NOTES

- 1 is shown as reference.
When selecting the unit models, avoid the Outdoor air temperature range shown by .
- 2 The above table shows the average value of conditions which may occur.