

Combination (%)	Capacity index (kW)	Outdoor air temp.		Indoor air temperature: °CDB											
				16.0		18.0		20.0		21.0		22.0		24.0	
				TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
130%	975 (122.20 kW)	-19.8	-20.0	57.8	12.8	57.6	13.9	57.4	15.1	57.3	15.7	57.2	16.2	56.9	17.4
		-18.8	-19.0	58.9	13.2	58.7	14.3	58.4	15.4	58.3	16.0	58.2	16.6	58.0	17.7
		-16.7	-17.0	61.1	13.9	60.9	15.0	60.7	16.1	60.6	16.7	60.5	17.2	60.2	18.3
		-13.7	-15.0	63.7	14.8	63.4	15.8	63.2	16.8	63.1	17.4	63.0	17.9	62.8	18.9
		-11.8	-13.0	66.4	15.6	66.2	16.6	66.0	17.6	65.9	18.1	65.7	18.6	65.5	19.6
		-9.8	-11.0	69.4	16.4	69.2	17.3	69.0	18.3	68.9	18.8	68.8	19.2	68.5	20.2
		-9.5	-10.0	71.1	16.8	70.8	17.7	70.6	18.6	70.5	19.1	70.4	19.6	70.2	20.5
		-8.5	-9.1	72.6	17.1	72.3	18.1	72.1	19.0	72.0	19.4	71.9	19.9	71.7	20.8
		-7.0	-7.6	75.2	17.7	75.0	18.6	74.7	19.5	74.6	19.9	74.5	20.4	74.3	21.2
		-5.0	-5.6	78.9	18.5	78.7	19.3	78.4	20.2	78.3	20.6	78.2	21.0	78.0	21.8
		-3.0	-3.7	82.6	19.2	82.4	20.0	82.2	20.8	82.1	21.2	82.0	21.6	81.7	22.4
		0.0	-0.7	89.1	20.3	88.8	21.0	88.6	21.7	88.5	22.1	88.4	22.5	88.2	23.2
		3.0	2.2	95.8	21.2	95.6	21.9	95.3	22.6	95.2	22.9	95.1	23.3	94.9	23.9
		5.0	4.1	101	21.8	100	22.4	100	23.1	99.9	23.4	99.8	23.7	99.6	24.4
		7.0	6.0	105	22.4	105	23.0	105	23.6	105	23.9	105	24.2	105	24.8
		9.0	7.9	111	22.9	110	23.5	110	24.1	110	24.4	110	24.6	106	24.1
		11.0	9.8	116	23.4	116	23.9	116	24.5	115	24.8	114	24.7	106	22.7
13.0	11.8	122	23.9	122	24.4	121	24.9	118	24.2	114	23.2	106	21.3		
15.0	13.7	128	24.3	128	24.8	122	23.7	118	22.8	114	21.9	106	20.1		
120%	900 (112.80 kW)	-19.8	-20.0	57.5	14.3	57.3	15.4	57.1	16.5	57.0	17.0	56.9	17.5	56.7	18.6
		-18.8	-19.0	58.6	14.7	58.4	15.7	58.2	16.8	58.1	17.3	57.9	17.8	57.7	18.9
		-16.7	-17.0	60.8	15.4	60.6	16.4	60.4	17.4	60.3	17.9	60.2	18.4	60.0	19.4
		-13.7	-15.0	63.4	16.2	63.1	17.1	62.9	18.1	62.8	18.6	62.7	19.1	62.5	20.0
		-11.8	-13.0	66.1	16.9	65.9	17.8	65.7	18.8	65.6	19.2	65.5	19.7	65.3	20.6
		-9.8	-11.0	69.1	17.7	68.9	18.5	68.7	19.4	68.6	19.9	68.5	20.3	68.3	21.2
		-9.5	-10.0	70.8	18.0	70.5	18.9	70.3	19.8	70.2	20.2	70.1	20.6	69.9	21.5
		-8.5	-9.1	72.3	18.4	72.0	19.2	71.8	20.0	71.7	20.5	71.6	20.9	71.4	21.7
		-7.0	-7.6	74.9	18.9	74.7	19.7	74.5	20.5	74.3	20.9	74.2	21.3	74.0	22.2
		-5.0	-5.6	78.6	19.6	78.4	20.4	78.2	21.2	78.1	21.5	78.0	21.9	77.7	22.7
		-3.0	-3.7	82.3	20.3	82.1	21.0	81.9	21.7	81.8	22.1	81.7	22.5	81.5	23.2
		0.0	-0.7	88.8	21.3	88.5	21.9	88.3	22.6	88.2	22.9	88.1	23.3	87.9	24.0
		3.0	2.2	95.5	22.1	95.3	22.8	95.1	23.4	95.0	23.7	94.9	24.0	94.7	24.6
		5.0	4.1	100	22.7	100.0	23.3	99.8	23.9	99.7	24.2	99.6	24.5	98.3	24.6
		7.0	6.0	105	23.2	105	23.8	105	24.3	105	24.6	105	24.9	98.3	23.2
		9.0	7.9	110	23.7	110	24.2	110	24.8	109	24.8	106	23.8	98.3	21.9
		11.0	9.8	116	24.1	115	24.7	113	24.3	109	23.4	106	22.4	98.3	20.6
13.0	11.8	122	24.6	120	24.6	113	22.8	109	22.0	106	21.1	98.3	19.4		
15.0	13.7	127	25.0	120	23.2	113	21.6	109	20.7	106	19.9	98.3	18.4		
110%	825 (103.40 kW)	-19.8	-20.0	57.2	15.9	57.0	16.9	56.9	17.8	56.8	18.3	56.7	18.8	56.5	19.8
		-18.8	-19.0	58.3	16.2	58.1	17.2	57.9	18.1	57.8	18.6	57.7	19.1	57.5	20.1
		-16.7	-17.0	60.5	16.9	60.3	17.8	60.1	18.7	60.1	19.2	60.0	19.7	59.8	20.6
		-13.7	-15.0	63.0	17.6	62.9	18.5	62.7	19.3	62.6	19.8	62.5	20.2	62.3	21.1
		-11.8	-13.0	65.8	18.3	65.6	19.1	65.4	20.0	65.3	20.4	65.2	20.8	65.1	21.6
		-9.8	-11.0	68.8	19.0	68.6	19.8	68.5	20.6	68.4	21.0	68.3	21.4	68.1	22.2
		-9.5	-10.0	70.4	19.3	70.3	20.1	70.1	20.9	70.0	21.3	69.9	21.7	69.7	22.4
		-8.5	-9.1	71.9	19.6	71.8	20.4	71.6	21.1	71.5	21.5	71.4	21.9	71.2	22.7
		-7.0	-7.6	74.6	20.1	74.4	20.8	74.2	21.6	74.1	22.0	74.0	22.3	73.8	23.1
		-5.0	-5.6	78.3	20.7	78.1	21.5	77.9	22.2	77.8	22.5	77.7	22.9	77.5	23.6
		-3.0	-3.7	82.0	21.3	81.8	22.0	81.7	22.7	81.6	23.0	81.5	23.4	81.3	24.0
		0.0	-0.7	88.4	22.2	88.3	22.9	88.1	23.5	88.0	23.8	87.9	24.1	87.7	24.7
		3.0	2.2	95.2	23.0	95.0	23.6	94.8	24.2	94.7	24.5	94.6	24.8	94.1	23.5
		5.0	4.1	99.9	23.5	99.7	24.1	99.5	24.6	99.4	24.9	99.3	25.2	99.1	25.9
		7.0	6.0	105	24.0	105	24.5	103	24.7	100	23.7	96.8	22.8	90.1	20.9
		9.0	7.9	110	24.5	110	25.0	103	23.2	100	22.3	96.8	21.4	90.1	19.7
		11.0	9.8	115	24.9	110	23.6	103	21.9	100	21.1	96.8	20.2	90.1	18.6
13.0	11.8	117	23.8	110	22.2	103	20.6	100	19.8	96.8	19.1	90.1	17.6		
15.0	13.7	117	22.5	110	20.9	103	19.5	100	18.7	96.8	18.0	90.1	16.6		
100%	750 (94.00 kW)	-19.8	-20.0	56.9	17.5	56.8	18.3	56.6	19.2	56.5	19.7	56.4	20.1	56.2	21.0
		-18.8	-19.0	58.0	17.7	57.8	18.6	57.6	19.5	57.5	19.9	57.4	20.4	57.3	21.2
		-16.7	-17.0	60.2	18.4	60.1	19.2	59.9	20.0	59.8	20.5	59.7	20.9	59.5	21.7
		-13.7	-15.0	62.7	19.0	62.6	19.8	62.4	20.6	62.3	21.0	62.2	21.4	62.0	22.2
		-11.8	-13.0	65.5	19.6	65.3	20.4	65.2	21.1	65.1	21.5	65.0	21.9	64.8	22.7
		-9.8	-11.0	68.5	20.2	68.4	21.0	68.2	21.7	68.1	22.1	68.0	22.4	67.8	23.2
		-9.5	-10.0	70.1	20.6	70.0	21.3	69.8	22.0	69.7	22.3	69.6	22.7	69.4	23.4
		-8.5	-9.1	71.6	20.8	71.5	21.5	71.3	22.2	71.2	22.6	71.1	22.9	70.9	23.6
		-7.0	-7.6	74.3	21.3	74.1	22.0	73.9	22.6	73.8	23.0	73.7	23.3	73.6	24.0
		-5.0	-5.6	78.0	21.9	77.8	22.5	77.6	23.2	77.5	23.5	77.5	23.8	77.3	24.4
		-3.0	-3.7	81.7	22.4	81.6	23.0	81.4	23.6	81.3	23.9	81.2	24.2	81.0	24.9
		0.0	-0.7	88.1	23.2	88.0	23.8	87.8	24.4	87.7	24.6	87.6	24.9	81.9	23.0
		3.0	2.2	94.9	24.0	94.7	24.5	94.0	24.8	91.0	23.8	88.0	22.9	81.9	21.0
		5.0	4.1	99.6	24.4	99.4	24.9	94.0	23.3	91.0	22.4	88.0	21.5	81.9	19.8
		7.0	6.0	105	24.9	100	23.7	94.0	22.0	91.0	21.1	88.0	20.3	81.9	18.7
		9.0	7.9	106	24.0	100	22.3	94.0	20.7	91.0	19.9	88.0	19.2	81.9	17.7
		11.0	9.8	106	22.6	100	21.1	94.0	19.6	91.0	18.8	88.0	18.1	81.9	16.7
13.0	11.8	106	21.2	100	19.8	94.0	18.4	91.0	17.8	88.0	17.1	81.9	15.8		
15.0	13.7	106	20.1	100	18.7	94.0	17.4	91.0	16.8	88.0	16.2	81.9	15.0		

NOTES

- █ is shown as reference.
When selecting the unit models, avoid the Outdoor air temperature range shown by █.
- The above table shows the average value of conditions which may occur.