

Combination (%)	Capacity index (kW)	Outdoor air temp.	Indoor air temperature: °CWB															
			14.0		16.0		18.0		19.0		20.0		22.0		24.0			
			TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI		
90%	720 (80.55 kW)	°CDB																
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW			
		10	54.4	7.36	64.8	8.87	75.3	10.48	80.6	11.30	85.8	12.15	96.3	13.88	106.7	15.64		
		12	54.4	7.48	64.8	9.03	75.3	10.67	80.6	11.51	85.8	12.38	96.3	14.14	106.7	15.94		
		14	54.4	7.61	64.8	9.19	75.3	10.87	80.6	11.73	85.8	12.61	96.3	14.41	106.7	16.24		
		16	54.4	7.74	64.8	9.36	75.3	11.07	80.6	11.96	85.8	12.86	96.3	14.69	106.7	16.56		
		18	54.4	7.88	64.8	9.54	75.3	11.29	80.6	12.19	85.8	13.11	96.3	14.99	106.7	17.50		
		20	54.4	8.03	64.8	9.73	75.3	11.52	80.6	12.44	85.8	13.60	96.3	16.10	106.7	18.82		
		21	54.4	8.10	64.8	9.82	75.3	11.71	80.6	12.87	85.8	14.09	96.3	16.68	106.7	19.50		
		23	54.4	8.26	64.8	10.23	75.3	12.54	80.6	13.78	85.8	15.09	96.3	17.89	105.6	20.50		
		25	54.4	8.70	64.8	10.92	75.3	13.40	80.6	14.74	85.8	16.15	96.3	19.16	104.0	21.40		
		27	54.4	9.26	64.8	11.64	75.3	14.31	80.6	15.75	85.8	17.26	96.3	20.50	102.5	22.30		
		29	54.4	9.85	64.8	12.41	75.3	15.27	80.6	16.82	85.8	18.44	96.3	21.91	101.0	23.20		
		31	54.4	10.47	64.8	13.21	75.3	16.28	80.6	17.94	85.8	19.68	96.3	23.41	99.5	24.11		
		33	54.4	11.13	64.8	14.06	75.3	17.35	80.6	19.12	85.8	20.99	95.8	24.8	98.0	25.0		
		35	54.4	11.81	64.8	14.95	75.3	18.47	80.6	20.38	85.8	22.38	94.4	25.7	96.5	25.9		
		37	54.4	12.54	64.8	15.89	75.3	19.66	80.6	21.70	85.8	23.8	92.9	26.6	95.0	26.9		
		39	54.4	13.30	64.8	16.89	75.3	20.93	80.6	23.11	85.8	25.4	91.4	27.6	93.5	27.8		
		42	54.4	14.84	64.8	18.90	75.3	23.5	80.6	25.93	85.8	28.5	89.1	29.6	91.2	29.8		
		44	54.4	16.01	64.8	20.42	75.3	25.4	80.6	28.07	85.0	30.7	86.3	30.9	87.2	32.9		
		46	54.4	17.25	64.8	22.04	74.3	27.1	79.5	27.79	75.6	27.8	75.7	27.8	75.9	27.9		
		80%	640 (71.60 kW)	°CDB														
				kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	
				10	48.3	6.53	57.6	7.82	66.9	9.19	71.6	9.90	76.3	10.62	85.6	12.11	94.9	13.65
				12	48.3	6.64	57.6	7.95	66.9	9.35	71.6	10.08	76.3	10.82	85.6	12.34	94.9	13.90
				14	48.3	6.75	57.6	8.09	66.9	9.52	71.6	10.26	76.3	11.02	85.6	12.58	94.9	14.17
16	48.3			6.86	57.6	8.24	66.9	9.70	71.6	10.46	76.3	11.23	85.6	12.82	94.9	14.45		
18	48.3			6.98	57.6	8.39	66.9	9.89	71.6	10.66	76.3	11.45	85.6	13.07	94.9	14.73		
20	48.3			7.10	57.6	8.55	66.9	10.08	71.6	10.87	76.3	11.68	85.6	13.55	94.9	15.76		
21	48.3			7.17	57.6	8.63	66.9	10.18	71.6	10.98	76.3	11.92	85.6	14.03	94.9	16.33		
23	48.3			7.30	57.6	8.80	66.9	10.67	71.6	11.69	76.3	12.76	85.6	15.04	94.9	17.50		
25	48.3			7.54	57.6	9.36	66.9	11.40	71.6	12.49	76.3	13.64	85.6	16.09	94.9	18.75		
27	48.3			8.02	57.6	9.97	66.9	12.16	71.6	13.33	76.3	14.57	85.6	17.20	94.9	20.05		
29	48.3			8.52	57.6	10.62	66.9	12.96	71.6	14.22	76.3	15.54	85.6	18.37	94.9	21.43		
31	48.3			9.04	57.6	11.29	66.9	13.80	71.6	15.15	76.3	16.57	85.6	19.60	94.9	22.89		
33	48.3			9.60	57.6	12.00	66.9	14.69	71.6	16.14	76.3	17.66	85.6	20.91	94.9	24.4		
35	48.3			10.18	57.6	12.75	66.9	15.63	71.6	17.18	76.3	18.81	85.6	22.29	94.2	25.7		
37	48.3			10.79	57.6	13.54	66.9	16.62	71.6	18.28	76.3	20.02	85.6	23.8	92.6	26.6		
39	48.3			11.43	57.6	14.37	66.9	17.67	71.6	19.45	76.3	21.31	85.6	25.3	91.1	27.5		
42	48.3			12.73	57.6	16.06	66.9	19.78	71.6	21.79	76.3	23.9	85.6	28.4	88.9	29.5		
44	48.3			13.72	57.6	17.33	66.9	21.37	71.6	23.56	76.3	25.9	85.0	30.7	86.2	30.9		
46	48.3			14.76	57.6	18.68	66.9	23.07	71.6	25.45	74.9	27.4	75.7	27.8	75.9	27.9		
70%	560 (62.65 kW)			°CDB														
				kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	
				10	42.3	5.74	50.4	6.81	58.6	7.95	62.7	8.55	66.7	9.15	74.9	10.41	83.0	11.70
				12	42.3	5.83	50.4	6.93	58.6	8.09	62.7	8.70	66.7	9.32	74.9	10.60	83.0	11.92
				14	42.3	5.92	50.4	7.04	58.6	8.23	62.7	8.85	66.7	9.49	74.9	10.80	83.0	12.15
		16	42.3	6.02	50.4	7.16	58.6	8.38	62.7	9.02	66.7	9.67	74.9	11.00	83.0	12.38		
		18	42.3	6.11	50.4	7.29	58.6	8.54	62.7	9.19	66.7	9.85	74.9	11.22	83.0	12.62		
		20	42.3	6.22	50.4	7.42	58.6	8.70	62.7	9.36	66.7	10.04	74.9	11.44	83.0	12.98		
		21	42.3	6.27	50.4	7.49	58.6	8.78	62.7	9.45	66.7	10.14	74.9	11.62	83.0	13.44		
		23	42.3	6.38	50.4	7.63	58.6	8.96	62.7	9.77	66.7	10.62	74.9	12.44	83.0	14.39		
		25	42.3	6.49	50.4	7.93	58.6	9.56	62.7	10.43	66.7	11.35	74.9	13.29	83.0	15.40		
		27	42.3	6.86	50.4	8.44	58.6	10.19	62.7	11.12	66.7	12.10	74.9	14.19	83.0	16.46		
		29	42.3	7.28	50.4	8.97	58.6	10.84	62.7	11.85	66.7	12.90	74.9	15.14	83.0	17.57		
		31	42.3	7.72	50.4	9.53	58.6	11.54	62.7	12.61	66.7	13.74	74.9	16.14	83.0	18.75		
		33	42.3	8.19	50.4	10.12	58.6	12.26	62.7	13.42	66.7	14.62	74.9	17.20	83.0	19.99		
		35	42.3	8.67	50.4	10.73	58.6	13.03	62.7	14.26	66.7	15.56	74.9	18.32	83.0	21.31		
		37	42.3	9.18	50.4	11.38	58.6	13.84	62.7	15.16	66.7	16.54	74.9	19.50	83.0	22.70		
		39	42.3	9.71	50.4	12.07	58.6	14.69	62.7	16.11	66.7	17.59	74.9	20.75	83.0	24.2		
		42	42.3	10.79	50.4	13.45	58.6	16.42	62.7	18.01	66.7	19.68	74.9	23.3	83.0	27.1		
		44	42.3	11.61	50.4	14.50	58.6	17.72	62.7	19.45	66.7	21.27	74.9	25.2	83.0	29.4		
		46	42.3	12.47	50.4	15.60	58.6	19.10	62.7	20.99	66.7	22.96	74.1	27.0	75.9	27.9		
		60%	480 (53.70 kW)	°CDB														
				kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	
				10	36.2	5.00	43.2	5.86	50.2	6.78	53.7	7.26	57.2	7.76	64.2	8.77	71.2	9.83
				12	36.2	5.07	43.2	5.95	50.2	6.90	53.7	7.39	57.2	7.89	64.2	8.93	71.2	10.01
				14	36.2	5.14	43.2	6.05	50.2	7.01	53.7	7.51	57.2	8.03	64.2	9.09	71.2	10.19
16	36.2			5.22	43.2	6.14	50.2	7.13	53.7	7.65	57.2	8.17	64.2	9.26	71.2	10.39		
18	36.2			5.30	43.2	6.25	50.2	7.26	53.7	7.78	57.2	8.32	64.2	9.43	71.2	10.59		
20	36.2			5.38	43.2	6.35	50.2	7.39	53.7	7.93	57.2	8.48	64.2	9.62	71.2	10.80		
21	36.2			5.42	43.2	6.41	50.2	7.45	53.7	8.00	57.2	8.56	64.2	9.71	71.2	10.90		
23	36.2			5.51	43.2	6.52	50.2	7.59	53.7	8.15	57.2	8.72	64.2	10.09	71.2	11.59		
25	36.2			5.60	43.2	6.64	50.2	7.89	53.7	8.57	57.2	9.27	64.2	10.77	71.2	12.39		
27	36.2			5.81	43.2	7.04	50.2	8.39	53.7	9.12	57.2	9.88	64.2	11.49	71.2	13.22		
29	36.2			6.15	43.2	7.47	50.2	8.92	53.7	9.70	57.2	10.51	64.2	12.24	71.2	14.10		
31	36.2			6.51	43.2	7.92	50.2	9.48	53.7	10.31	57.2	11.18	64.2	13.03	71.2	15.02		
33	36.2			6.89	43.2	8.40	50.2	10.06	53.7	10.95	57.2	11.88	64.2	13.86	71.2	16.00		
35	36.2			7.29	43.2	8.90	50.2	10.67	53.7	11.63	57.2	12.62	64.2	14.74	71.2	17.03		
37	36.2			7.70	43.2	9.42	50.2	11.32	53.7	12.34	57.2	13.40	64.2	15.67	71.2	18.12		
39	36.2			8.14	43.2	9.97	50.2	12.00	53.7	13.09	57.2	14.23	64.2	16.65	71.2	19.27		
42	36.2			9.02	43.2	11.09	50.2	13.38	53.7	14.60	57.2	15.89	64.2	18.63	71.2	21.59		
44	36.2			9.68	43.2	11.93	50.2	14.41	53.7	15.75	57.2	17.15	64.2	20.13	71.2	23.35		
46	36.2			10.39	43.2	12.81	50.2	15.51	53.7	16.96	57.2	18.48	64.2	21.72	71.2	25.2		
50%	400 (44.75 kW)			°CDB														
				kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	
				10	30.20	4.29	36.0	4.97	41.8	5.69	44.8	6.06	47.7	6.44	53.5	7.23	59.3	8.06
				12														