

Combination (%)	Capacity index (kW)	Outdoor air temp.		Indoor air temperature: °CDB												
				16.0		18.0		20.0		21.0		22.0		24.0		
				TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	
130%	1040 (130.65 kW)	°CDB	°CWB													
		-19.8	-20.0	64.3	15.4	64.1	16.6	63.9	17.9	63.7	18.5	63.6	19.1	63.4	20.3	
		-18.8	-19.0	65.5	15.8	65.3	17.0	65.0	18.2	64.9	18.8	64.8	19.4	64.5	20.7	
		-16.7	-17.0	68.0	16.7	67.8	17.8	67.5	19.0	67.4	19.6	67.3	20.1	67.1	21.3	
		-13.7	-15.0	70.8	17.5	70.6	18.6	70.3	19.7	70.2	20.3	70.1	20.9	69.9	22.0	
		-11.8	-13.0	73.9	18.4	73.7	19.5	73.4	20.5	73.3	21.1	73.2	21.6	73.0	22.6	
		-9.8	-11.0	77.3	19.3	77.1	20.3	76.8	21.3	76.7	21.8	76.6	22.3	76.3	23.3	
		-9.5	-10.0	79.1	19.7	78.8	20.7	78.6	21.7	78.5	22.2	78.4	22.7	78.1	23.7	
		-8.5	-9.1	80.8	20.1	80.5	21.0	80.3	22.0	80.2	22.5	80.0	23.0	79.8	23.9	
		-7.0	-7.6	83.7	20.7	83.4	21.6	83.2	22.6	83.1	23.0	83.0	23.5	82.7	24.4	
		-5.0	-5.6	87.8	21.5	87.6	22.4	87.3	23.3	87.2	23.7	87.1	24.2	86.9	25.1	
		-3.0	-3.7	92.0	22.3	91.8	23.1	91.5	24.0	91.4	24.4	91.3	24.8	91.1	25.6	
		0.0	-0.7	99.2	23.4	98.9	24.2	98.7	25.0	98.6	25.4	98.4	25.7	98.2	26.5	
		3.0	2.2	107	24.4	106	25.1	106	25.9	106	26.2	106	26.6	106	27.3	
		5.0	4.1	112	25.0	112	25.7	111	26.4	111	26.8	111	27.1	111	27.8	
		7.0	6.0	117	25.6	117	26.3	117	26.9	117	27.3	117	27.6	114	27.2	
		9.0	7.9	123	26.2	123	26.8	123	27.4	123	27.8	122	28.0	114	25.6	
11.0	9.8	129	26.7	129	27.3	129	27.9	126	27.5	122	26.3	114	24.2			
13.0	11.8	136	27.3	136	27.8	131	26.8	126	25.8	122	24.8	114	22.7			
15.0	13.7	142	27.7	139	27.3	131	25.3	126	24.3	122	23.4	114	21.5			
120%	960 (120.60 kW)	-19.8	-20.0	64.0	17.1	63.8	18.2	63.6	19.3	63.5	19.9	63.4	20.5	63.1	21.6	
		-18.8	-19.0	65.2	17.4	65.0	18.6	64.7	19.7	64.6	20.2	64.5	20.8	64.3	21.9	
		-16.7	-17.0	67.7	18.2	67.5	19.3	67.3	20.4	67.1	20.9	67.0	21.4	66.8	22.5	
		-13.7	-15.0	70.5	19.0	70.3	20.1	70.1	21.1	69.9	21.6	69.8	22.1	69.6	23.1	
		-11.8	-13.0	73.6	19.8	73.4	20.8	73.1	21.8	73.0	22.3	72.9	22.8	72.7	23.8	
		-9.8	-11.0	77.0	20.6	76.7	21.6	76.5	22.5	76.4	23.0	76.3	23.4	76.1	24.4	
		-9.5	-10.0	78.8	21.0	78.5	21.9	78.3	22.9	78.2	23.3	78.1	23.8	77.9	24.7	
		-8.5	-9.1	80.4	21.4	80.2	22.3	80.0	23.2	79.9	23.6	79.8	24.1	79.5	25.0	
		-7.0	-7.6	83.4	22.0	83.1	22.8	82.9	23.7	82.8	24.1	82.7	24.5	82.5	25.4	
		-5.0	-5.6	87.5	22.7	87.3	23.5	87.0	24.4	86.9	24.8	86.8	25.2	86.6	26.0	
		-3.0	-3.7	91.7	23.4	91.5	24.2	91.2	25.0	91.1	25.4	91.0	25.8	90.8	26.5	
		0.0	-0.7	98.8	24.5	98.6	25.2	98.4	25.9	98.3	26.3	98.2	26.6	97.9	27.3	
		3.0	2.2	106	25.4	106	26.1	106	26.7	106	27.1	106	27.4	105	27.9	
		5.0	4.1	112	26.0	111	26.6	111	27.2	111	27.6	111	27.9	105	26.3	
		7.0	6.0	117	26.5	117	27.1	117	27.7	117	28.0	113	27.0	105	24.7	
		9.0	7.9	123	27.0	123	27.6	121	27.5	117	26.4	113	25.4	105	23.3	
		11.0	9.8	129	27.5	128	28.0	121	25.9	117	24.9	113	23.9	105	22.0	
13.0	11.8	136	28.0	128	26.3	121	24.3	117	23.4	113	22.5	105	20.7			
15.0	13.7	136	26.6	128	24.8	121	23.0	117	22.1	113	21.2	105	19.6			
110%	880 (110.55 kW)	-19.8	-20.0	63.7	18.7	63.5	19.8	63.3	20.8	63.2	21.3	63.1	21.9	62.9	22.9	
		-18.8	-19.0	64.8	19.1	64.6	20.1	64.4	21.1	64.3	21.6	64.2	22.1	64.0	23.2	
		-16.7	-17.0	67.4	19.8	67.2	20.8	67.0	21.8	66.9	22.3	66.8	22.7	66.6	23.7	
		-13.7	-15.0	70.2	20.5	70.0	21.5	69.8	22.4	69.7	22.9	69.6	23.4	69.4	24.3	
		-11.8	-13.0	73.3	21.3	73.1	22.2	72.9	23.1	72.8	23.5	72.7	24.0	72.4	24.9	
		-9.8	-11.0	76.6	22.0	76.4	22.9	76.2	23.7	76.1	24.1	76.0	24.6	75.8	25.4	
		-9.5	-10.0	78.4	22.4	78.2	23.2	78.0	24.0	77.9	24.5	77.8	24.9	77.6	25.7	
		-8.5	-9.1	80.1	22.7	79.9	23.5	79.7	24.3	79.6	24.7	79.5	25.1	79.3	26.0	
		-7.0	-7.6	83.0	23.2	82.8	24.0	82.6	24.8	82.5	25.2	82.4	25.6	82.2	26.4	
		-5.0	-5.6	87.2	23.9	87.0	24.7	86.8	25.4	86.7	25.8	86.6	26.2	86.4	26.9	
		-3.0	-3.7	91.4	24.6	91.2	25.3	91.0	26.0	90.9	26.3	90.8	26.7	90.5	27.4	
		0.0	-0.7	98.5	25.5	98.3	26.2	98.1	26.8	98.0	27.2	97.9	27.5	96.3	27.5	
		3.0	2.2	106	26.4	106	27.0	106	27.6	106	27.9	103	27.4	96.3	25.1	
		5.0	4.1	111	26.9	111	27.5	111	27.9	107	26.8	103	25.7	96.3	23.6	
		7.0	6.0	117	27.4	117	28.0	111	26.3	107	25.3	103	24.2	96.3	22.3	
		9.0	7.9	123	27.9	118	26.7	111	24.7	107	23.8	103	22.9	96.3	21.0	
		11.0	9.8	125	27.0	118	25.1	111	23.3	107	22.4	103	21.6	96.3	19.9	
13.0	11.8	125	25.4	118	23.6	111	21.9	107	21.1	103	20.3	96.3	18.7			
15.0	13.7	125	23.9	118	22.3	111	20.7	107	20.0	103	19.2	96.3	17.7			
100%	800 (100.50 kW)	-19.8	-20.0	63.4	20.4	63.2	21.3	63.0	22.3	62.9	22.8	62.8	23.2	62.6	24.2	
		-18.8	-19.0	64.5	20.7	64.3	21.6	64.2	22.6	64.1	23.0	64.0	23.5	63.8	24.4	
		-16.7	-17.0	67.0	21.4	66.9	22.3	66.7	23.2	66.6	23.6	66.5	24.0	66.3	24.9	
		-13.7	-15.0	69.9	22.0	69.7	22.9	69.5	23.7	69.4	24.2	69.3	24.6	69.1	25.5	
		-11.8	-13.0	72.9	22.7	72.8	23.5	72.6	24.3	72.5	24.7	72.4	25.2	72.2	26.0	
		-9.8	-11.0	76.3	23.4	76.1	24.2	75.9	24.9	75.9	25.3	75.8	25.7	75.6	26.5	
		-9.5	-10.0	78.1	23.7	77.9	24.5	77.7	25.2	77.6	25.6	77.6	26.0	77.4	26.8	
		-8.5	-9.1	79.8	24.0	79.6	24.7	79.4	25.5	79.3	25.9	79.2	26.2	79.0	27.0	
		-7.0	-7.6	82.7	24.5	82.5	25.2	82.3	25.9	82.2	26.3	82.1	26.6	82.0	27.4	
		-5.0	-5.6	86.8	25.1	86.7	25.8	86.5	26.5	86.4	26.8	86.3	27.2	86.1	27.8	
		-3.0	-3.7	91.0	25.7	90.9	26.3	90.7	27.0	90.6	27.3	90.5	27.6	87.6	26.9	
		0.0	-0.7	98.2	26.6	98.0	27.2	97.8	27.8	97.3	27.9	94.0	26.7	87.6	24.5	
		3.0	2.2	106	27.3	106	27.9	101	26.4	97.3	25.4	94.0	24.4	87.6	22.4	
		5.0	4.1	111	27.8	107	26.8	101	24.9	97.3	23.9	94.0	23.0	87.6	21.1	
		7.0	6.0	113	27.1	107	25.2	101	23.4	97.3	22.5	94.0	21.6	87.6	19.9	
		9.0	7.9	113	25.5	107	23.8	101	22.1	97.3	21.3	94.0	20.4	87.6	18.8	
		11.0	9.8	113	24.1	107	22.4	101	20.8	97.3	20.1	94.0	19.3	87.6	17.8	
13.0	11.8	113	22.6	107	21.1	101	19.6	97.3	18.9	94.0	18.2	87.6	16.8			
15.0	13.7	113	21.4	107	20.0	101	18.6	97.3	17.9	94.0	17.2	87.6	15.9			

NOTES

- █ is shown as reference.
When selecting the unit models, avoid the Outdoor air temperature range shown by █.
- The above table shows the average value of conditions which may occur.