

Combination (%)	Capacity index (kW)	Outdoor air temp.		Indoor air temperature: °CDB											
				16.0		18.0		20.0		21.0		22.0		24.0	
				TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
130%	1105 (138.45 kW)	-19.8	-20.0	65.1	14.4	64.9	15.7	64.6	17.1	64.5	17.7	64.4	18.4	64.1	19.7
		-18.8	-19.0	66.3	14.8	66.0	16.2	65.8	17.5	65.7	18.1	65.5	18.8	65.3	20.1
		-16.7	-17.0	68.8	15.8	68.6	17.0	68.3	18.3	68.2	18.9	68.1	19.5	67.8	20.8
		-13.7	-15.0	71.7	16.7	71.4	17.9	71.2	19.1	71.0	19.7	70.9	20.3	70.7	21.5
		-11.8	-13.0	74.8	17.6	74.5	18.8	74.3	19.9	74.2	20.5	74.0	21.1	73.8	22.2
		-9.8	-11.0	78.2	18.6	77.9	19.7	77.7	20.8	77.6	21.3	77.4	21.9	77.2	23.0
		-9.5	-10.0	80.0	19.0	79.8	20.1	79.5	21.2	79.4	21.7	79.2	22.2	79.0	23.3
		-8.5	-9.1	81.7	19.4	81.4	20.5	81.2	21.5	81.1	22.1	80.9	22.6	80.7	23.6
		-7.0	-7.6	84.6	20.1	84.4	21.1	84.1	22.1	84.0	22.6	83.9	23.1	83.6	24.2
		-5.0	-5.6	88.8	21.0	88.6	22.0	88.3	22.9	88.2	23.4	88.1	23.9	87.8	24.8
		-3.0	-3.7	93.1	21.8	92.8	22.7	92.6	23.6	92.4	24.1	92.3	24.6	92.0	25.5
		0.0	-0.7	100	23.0	100	23.9	99.8	24.7	99.6	25.1	99.5	25.6	99.3	26.4
		3.0	2.2	108	24.1	108	24.9	107	25.7	107	26.1	107	26.5	107	27.3
		5.0	4.1	113	24.8	113	25.5	113	26.3	113	26.7	112	27.0	112	27.8
		7.0	6.0	119	25.4	118	26.2	118	26.9	118	27.2	118	27.6	118	28.3
		9.0	7.9	125	26.1	124	26.7	124	27.4	124	27.7	124	28.1	121	27.7
		11.0	9.8	131	26.6	130	27.3	130	27.9	130	28.2	130	28.5	121	26.1
13.0	11.8	137	27.2	137	27.8	137	28.4	134	27.9	130	26.7	121	24.6		
15.0	13.7	144	27.7	144	28.3	138	27.3	134	26.3	130	25.2	121	23.2		
120%	1020 (127.80 kW)	-19.8	-20.0	64.8	16.2	64.6	17.4	64.3	18.7	64.2	19.3	64.1	19.9	63.9	21.1
		-18.8	-19.0	66.0	16.6	65.7	17.8	65.5	19.0	65.4	19.6	65.3	20.2	65.0	21.4
		-16.7	-17.0	68.5	17.5	68.3	18.6	68.0	19.8	67.9	20.3	67.8	20.9	67.6	22.1
		-13.7	-15.0	71.3	18.3	71.1	19.4	70.9	20.5	70.7	21.1	70.6	21.6	70.4	22.8
		-11.8	-13.0	74.5	19.2	74.2	20.2	74.0	21.3	73.9	21.8	73.7	22.4	73.5	23.4
		-9.8	-11.0	77.9	20.0	77.6	21.1	77.4	22.1	77.3	22.6	77.2	23.1	76.9	24.1
		-9.5	-10.0	79.7	20.5	79.4	21.5	79.2	22.5	79.1	22.9	79.0	23.4	78.7	24.4
		-8.5	-9.1	81.4	20.9	81.1	21.8	80.9	22.8	80.8	23.3	80.6	23.8	80.4	24.7
		-7.0	-7.6	84.3	21.5	84.1	22.4	83.8	23.3	83.7	23.8	83.6	24.3	83.4	25.2
		-5.0	-5.6	88.5	22.3	88.2	23.2	88.0	24.1	87.9	24.5	87.8	25.0	87.5	25.8
		-3.0	-3.7	92.7	23.0	92.5	23.9	92.2	24.7	92.1	25.2	92.0	25.6	91.8	26.4
		0.0	-0.7	99.9	24.2	99.7	25.0	99.5	25.7	99.3	26.1	99.2	26.5	99.0	27.3
		3.0	2.2	108	25.2	107	25.9	107	26.6	107	27.0	107	27.4	107	28.1
		5.0	4.1	113	25.8	113	26.5	112	27.2	112	27.5	112	27.9	111	28.4
		7.0	6.0	118	26.4	118	27.1	118	27.7	118	28.0	118	28.4	111	26.7
		9.0	7.9	124	27.0	124	27.6	124	28.2	124	28.5	120	27.4	111	25.2
		11.0	9.8	130	27.5	130	28.1	128	28.0	124	26.9	120	25.8	111	23.7
13.0	11.8	137	28.0	136	28.4	128	26.3	124	25.3	120	24.3	111	22.3		
15.0	13.7	144	28.5	136	26.7	128	24.8	124	23.9	120	23.0	111	21.1		
110%	935 (117.15 kW)	-19.8	-20.0	64.4	18.0	64.2	19.1	64.0	20.3	63.9	20.8	63.8	21.4	63.6	22.5
		-18.8	-19.0	65.6	18.4	65.4	19.5	65.2	20.6	65.1	21.1	65.0	21.7	64.7	22.8
		-16.7	-17.0	68.2	19.1	67.9	20.2	67.7	21.3	67.6	21.8	67.5	22.3	67.3	23.4
		-13.7	-15.0	71.0	19.9	70.8	21.0	70.6	22.0	70.4	22.5	70.3	23.0	70.1	24.0
		-11.8	-13.0	74.1	20.7	73.9	21.7	73.7	22.7	73.6	23.2	73.5	23.6	73.2	24.6
		-9.8	-11.0	77.5	21.5	77.3	22.5	77.1	23.4	77.0	23.8	76.9	24.3	76.6	25.2
		-9.5	-10.0	79.3	21.9	79.1	22.8	78.9	23.7	78.8	24.2	78.7	24.6	78.5	25.5
		-8.5	-9.1	81.0	22.3	80.8	23.2	80.6	24.0	80.5	24.5	80.4	24.9	80.1	25.8
		-7.0	-7.6	84.0	22.8	83.7	23.7	83.5	24.6	83.4	25.0	83.3	25.4	83.1	26.3
		-5.0	-5.6	88.1	23.6	87.9	24.4	87.7	25.2	87.6	25.6	87.5	26.0	87.3	26.8
		-3.0	-3.7	92.4	24.3	92.2	25.1	91.9	25.8	91.8	26.2	91.7	26.6	91.5	27.4
		0.0	-0.7	99.6	25.3	99.4	26.0	99.2	26.7	99.0	27.1	98.9	27.5	98.7	28.2
		3.0	2.2	107	26.2	107	26.9	107	27.6	107	27.9	107	28.2	107	27.1
		5.0	4.1	112	26.8	112	27.4	112	28.1	112	28.4	110	27.8	102	25.5
		7.0	6.0	118	27.4	118	28.0	117	28.4	113	27.3	110	26.2	102	24.1
		9.0	7.9	124	27.9	124	28.4	117	26.7	113	25.7	110	24.7	102	22.7
		11.0	9.8	130	28.4	125	27.2	117	25.2	113	24.2	110	23.3	102	21.4
13.0	11.8	132	27.4	125	25.5	117	23.7	113	22.8	110	21.9	102	20.2		
15.0	13.7	132	25.8	125	24.1	117	22.4	113	21.6	110	20.8	102	19.1		
100%	850 (106.50 kW)	-19.8	-20.0	64.1	19.8	63.9	20.8	63.7	21.8	63.6	22.4	63.5	22.9	63.3	23.9
		-18.8	-19.0	65.3	20.1	65.1	21.1	64.9	22.1	64.8	22.6	64.7	23.2	64.5	24.2
		-16.7	-17.0	67.8	20.8	67.6	21.8	67.4	22.8	67.3	23.3	67.2	23.7	67.0	24.7
		-13.7	-15.0	70.6	21.6	70.4	22.5	70.3	23.4	70.2	23.9	70.1	24.3	69.9	25.3
		-11.8	-13.0	73.8	22.3	73.6	23.2	73.4	24.1	73.3	24.5	73.2	24.9	73.0	25.8
		-9.8	-11.0	77.2	23.0	77.0	23.9	76.8	24.7	76.7	25.1	76.6	25.5	76.4	26.4
		-9.5	-10.0	79.0	23.4	78.8	24.2	78.6	25.0	78.5	25.4	78.4	25.8	78.2	26.7
		-8.5	-9.1	80.7	23.7	80.5	24.5	80.3	25.3	80.2	25.7	80.1	26.1	79.9	26.9
		-7.0	-7.6	83.6	24.2	83.4	25.0	83.2	25.8	83.1	26.1	83.0	26.5	82.8	27.3
		-5.0	-5.6	87.8	24.9	87.6	25.6	87.4	26.4	87.3	26.7	87.2	27.1	87.0	27.8
		-3.0	-3.7	92.0	25.5	91.8	26.2	91.6	26.9	91.5	27.3	91.4	27.6	91.2	28.3
		0.0	-0.7	99.2	26.5	99.0	27.1	98.8	27.8	98.7	28.1	98.6	28.4	98.8	26.5
		3.0	2.2	107	27.3	107	27.9	106	28.5	103	27.4	99.7	26.3	92.8	24.2
		5.0	4.1	112	27.8	112	28.4	107	26.9	103	25.8	99.7	24.8	92.8	22.8
		7.0	6.0	118	28.3	113	27.3	107	25.3	103	24.3	99.7	23.4	92.8	21.5
		9.0	7.9	120	27.6	113	25.7	107	23.9	103	23.0	99.7	22.1	92.8	20.3
		11.0	9.8	120	26.0	113	24.2	107	22.5	103	21.7	99.7	20.9	92.8	19.2
13.0	11.8	120	24.4	113	22.8	107	21.2	103	20.4	99.7	19.7	92.8	18.2		
15.0	13.7	120	23.1	113	21.6	107	20.1	103	19.4	99.7	18.6	92.8	17.2		

NOTES

1 [ ] is shown as reference.

When selecting the unit models, avoid the Outdoor air temperature range shown by [ ].

2 The above table shows the average value of conditions which may occur.