

Combination (%)	Capacity index (kW)	Outdoor air temp.		Indoor air temperature: °CDB											
				16.0		18.0		20.0		21.0		22.0		24.0	
				TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
130%	1170 (146.90 kW)	-19.8	-20.0	66.0	13.2	65.7	14.6	65.4	16.0	65.3	16.7	65.1	17.5	64.9	18.9
		-18.8	-19.0	67.1	13.6	66.9	15.0	66.6	16.4	66.5	17.1	66.3	17.9	66.0	19.3
		-16.7	-17.0	69.7	14.6	69.4	16.0	69.2	17.3	69.0	18.0	68.9	18.7	68.6	20.0
		-13.7	-15.0	72.6	15.6	72.3	16.9	72.0	18.2	71.9	18.8	71.7	19.5	71.5	20.8
		-11.8	-13.0	75.7	16.6	75.4	17.9	75.2	19.1	75.0	19.7	74.9	20.3	74.6	21.6
		-9.8	-11.0	79.1	17.6	78.9	18.8	78.6	20.0	78.5	20.6	78.3	21.2	78.1	22.3
		-9.5	-10.0	81.0	18.1	80.7	19.3	80.4	20.4	80.3	21.0	80.1	21.6	79.9	22.7
		-8.5	-9.1	82.7	18.6	82.4	19.7	82.1	20.8	82.0	21.4	81.9	21.9	81.6	23.1
		-7.0	-7.6	85.6	19.3	85.4	20.4	85.1	21.5	85.0	22.0	84.8	22.6	84.6	23.6
		-5.0	-5.6	89.9	20.3	89.6	21.3	89.3	22.3	89.2	22.8	89.0	23.3	88.8	24.4
		-3.0	-3.7	94.1	21.1	93.9	22.1	93.6	23.1	93.4	23.6	93.3	24.1	93.0	25.0
		0.0	-0.7	101	22.4	101	23.3	101	24.2	101	24.7	101	25.1	100	26.1
		3.0	2.2	109	23.6	109	24.4	109	25.3	108	25.7	108	26.1	108	27.0
		5.0	4.1	114	24.3	114	25.1	114	25.9	114	26.3	114	26.7	113	27.5
		7.0	6.0	120	25.0	120	25.8	119	26.5	119	26.9	119	27.3	119	28.1
		9.0	7.9	126	25.7	126	26.4	125	27.1	125	27.5	125	27.8	125	28.6
		11.0	9.8	132	26.3	132	27.0	131	27.7	131	28.0	131	28.4	128	28.0
13.0	11.8	139	26.9	138	27.6	138	28.2	138	28.5	137	28.7	128	26.4		
15.0	13.7	145	27.5	145	28.1	145	28.7	142	28.2	137	27.1	128	24.9		
120%	1080 (135.60 kW)	-19.8	-20.0	65.6	15.1	65.3	16.4	65.1	17.7	65.0	18.4	64.8	19.1	64.6	20.4
		-18.8	-19.0	66.8	15.5	66.5	16.8	66.3	18.1	66.1	18.8	66.0	19.4	65.8	20.7
		-16.7	-17.0	69.3	16.4	69.1	17.7	68.8	18.9	68.7	19.5	68.6	20.2	68.3	21.4
		-13.7	-15.0	72.2	17.4	71.9	18.6	71.7	19.7	71.6	20.3	71.4	20.9	71.2	22.1
		-11.8	-13.0	75.3	18.3	75.1	19.4	74.8	20.6	74.7	21.1	74.6	21.7	74.3	22.9
		-9.8	-11.0	78.8	19.2	78.5	20.3	78.3	21.4	78.1	21.9	78.0	22.5	77.8	23.6
		-9.5	-10.0	80.6	19.7	80.3	20.7	80.1	21.8	80.0	22.3	79.8	22.9	79.6	23.9
		-8.5	-9.1	82.3	20.1	82.0	21.1	81.8	22.2	81.7	22.7	81.5	23.2	81.3	24.2
		-7.0	-7.6	85.3	20.8	85.0	21.8	84.8	22.8	84.6	23.3	84.5	23.8	84.3	24.8
		-5.0	-5.6	89.5	21.6	89.2	22.6	89.0	23.5	88.9	24.0	88.7	24.5	88.5	25.4
		-3.0	-3.7	93.8	22.4	93.5	23.4	93.3	24.3	93.1	24.7	93.0	25.2	92.8	26.1
		0.0	-0.7	101	23.7	101	24.5	101	25.3	100	25.7	100	26.2	100	27.0
		3.0	2.2	109	24.7	108	25.5	108	26.3	108	26.7	108	27.1	108	27.8
		5.0	4.1	114	25.4	114	26.2	114	26.9	113	27.3	113	27.6	113	28.4
		7.0	6.0	120	26.0	119	26.8	119	27.5	119	27.8	119	28.2	118	28.7
		9.0	7.9	126	26.7	125	27.3	125	28.0	125	28.3	125	28.7	118	27.0
		11.0	9.8	132	27.2	131	27.9	131	28.5	131	28.8	127	27.7	118	25.5
13.0	11.8	138	27.8	138	28.4	136	28.3	131	27.2	127	26.1	118	24.0		
15.0	13.7	145	28.3	144	28.7	136	26.7	131	25.7	127	24.7	118	22.7		
110%	990 (124.30 kW)	-19.8	-20.0	65.2	17.0	65.0	18.2	64.8	19.4	64.6	20.1	64.5	20.7	64.3	21.9
		-18.8	-19.0	66.4	17.4	66.2	18.6	65.9	19.8	65.8	20.4	65.7	21.0	65.5	22.2
		-16.7	-17.0	69.0	18.3	68.7	19.4	68.5	20.5	68.4	21.1	68.3	21.7	68.0	22.8
		-13.7	-15.0	71.8	19.1	71.6	20.2	71.4	21.3	71.2	21.8	71.1	22.4	70.9	23.5
		-11.8	-13.0	75.0	20.0	74.7	21.0	74.5	22.1	74.4	22.6	74.3	23.1	74.0	24.1
		-9.8	-11.0	78.4	20.8	78.2	21.8	77.9	22.8	77.8	23.3	77.7	23.8	77.5	24.8
		-9.5	-10.0	80.2	21.2	80.0	22.2	79.8	23.2	79.7	23.7	79.5	24.2	79.3	25.1
		-8.5	-9.1	81.9	21.6	81.7	22.6	81.5	23.5	81.4	24.0	81.2	24.5	81.0	25.4
		-7.0	-7.6	84.9	22.2	84.7	23.1	84.4	24.1	84.3	24.5	84.2	25.0	84.0	25.9
		-5.0	-5.6	89.1	23.0	88.9	23.9	88.7	24.8	88.5	25.2	88.4	25.6	88.2	26.5
		-3.0	-3.7	93.4	23.8	93.2	24.6	92.9	25.4	92.8	25.8	92.7	26.3	92.5	27.1
		0.0	-0.7	101	24.9	100	25.6	100	26.4	100	26.8	100.0	27.2	99.8	27.9
		3.0	2.2	108	25.9	108	26.6	108	27.3	108	27.7	108	28.0	107	28.7
		5.0	4.1	114	26.5	113	27.2	113	27.8	113	28.2	113	28.5	108	27.4
		7.0	6.0	119	27.1	119	27.7	119	28.4	119	28.7	116	28.1	108	25.8
		9.0	7.9	125	27.6	125	28.2	124	28.7	120	27.6	116	26.5	108	24.4
		11.0	9.8	131	28.2	131	28.7	124	27.1	120	26.0	116	25.0	108	23.0
13.0	11.8	138	28.7	132	27.4	124	25.5	120	24.5	116	23.6	108	21.7		
15.0	13.7	140	27.8	132	25.9	124	24.1	120	23.2	116	22.3	108	20.6		
100%	900 (113.00 kW)	-19.8	-20.0	64.9	19.0	64.6	20.1	64.4	21.2	64.3	21.7	64.2	22.3	64.0	23.4
		-18.8	-19.0	66.0	19.3	65.8	20.4	65.6	21.5	65.5	22.0	65.4	22.6	65.2	23.6
		-16.7	-17.0	68.6	20.1	68.4	21.1	68.2	22.2	68.1	22.7	68.0	23.2	67.8	24.2
		-13.7	-15.0	71.5	20.9	71.2	21.8	71.0	22.8	70.9	23.3	70.8	23.8	70.6	24.8
		-11.8	-13.0	74.6	21.6	74.4	22.6	74.2	23.5	74.1	24.0	74.0	24.5	73.8	25.4
		-9.8	-11.0	78.0	22.4	77.8	23.3	77.6	24.2	77.5	24.7	77.4	25.1	77.2	26.0
		-9.5	-10.0	79.9	22.8	79.7	23.7	79.4	24.6	79.3	25.0	79.2	25.4	79.0	26.3
		-8.5	-9.1	81.6	23.1	81.4	24.0	81.1	24.9	81.0	25.3	80.9	25.7	80.7	26.6
		-7.0	-7.6	84.5	23.7	84.3	24.5	84.1	25.4	84.0	25.8	83.9	26.2	83.7	27.0
		-5.0	-5.6	88.8	24.4	88.5	25.2	88.3	26.0	88.2	26.4	88.1	26.8	87.9	27.6
		-3.0	-3.7	93.0	25.1	92.8	25.9	92.6	26.6	92.5	27.0	92.4	27.4	92.2	28.1
		0.0	-0.7	100	26.1	100	26.8	99.9	27.5	99.8	27.8	99.7	28.2	98.5	28.4
		3.0	2.2	108	27.0	108	27.7	108	28.3	107	28.6	106	28.3	98.5	26.0
		5.0	4.1	113	27.6	113	28.2	113	28.8	109	27.7	106	26.6	98.5	24.5
		7.0	6.0	119	28.1	119	28.7	113	27.2	109	26.1	106	25.1	98.5	23.1
		9.0	7.9	125	28.6	120	27.6	113	25.6	109	24.7	106	23.7	98.5	21.8
		11.0	9.8	128	27.9	120	26.0	113	24.2	109	23.3	106	22.4	98.5	20.7
13.0	11.8	128	26.3	120	24.5	113	22.8	109	22.0	106	21.1	98.5	19.5		
15.0	13.7	128	24.8	120	23.2	113	21.6	109	20.8	106	20.0	98.5	18.5		

NOTES

1 [] is shown as reference.

When selecting the unit models, avoid the Outdoor air temperature range shown by [].

2 The above table shows the average value of conditions which may occur.