

Cooling

		Indoor air temperature													
Unit size	Fan speed	14,0 [°C WB]		16,0 [°C WB]		18,0 [°C WB]		19,0 [°C WB]		20,0 [°C WB]		22,0 [°C WB]		24,0 [°C WB]	
		20,0 [°C DB]		23,0 [°C DB]		26,0 [°C DB]		27,0 [°C DB]		28,0 [°C DB]		30,0 [°C DB]		32,0 [°C DB]	
		TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
200	H	12,4	11,2	16,4	13,8	20,4	16,2	22,4	16,9	24,4	17,5	28,8	18,9	33,5	20,2
	M	Correction factor -0.85 x H-													
	L	Correction factor -0.76 x H-													
250	H	16,2	14,3	20,8	17,3	25,6	20,1	28,0	20,9	30,5	21,7	35,8	23,1	41,4	24,1
	M	Correction factor -0.86 x H-													
	L	Correction factor -0.75 x H-													

Notes

- 1) TC: Total capacity [kW]
SHC: Sensible heat capacity [kW]
H: High
M: Medium
L: Low

2) Outdoor temperature -35-°C DB

Heating

Unit size	Fan speed	Indoor air temperature					
		16,0 [°C DB]		18,0 [°C DB]		20,0 [°C DB]	
		22,0 [°C DB]		24,0 [°C DB]			
		TC	TC	TC	TC	TC	TC
200	H	28,9	26,9	25,0	24,0	23,1	21,2
	M	Correction factor -0.82 × H-					
	L	Correction factor -0.72 × H-					
250	H	36,4	33,9	31,5	30,3	29,1	26,7
	M	Correction factor -0.86 × H-					
	L	Correction factor -0.70 × H-					

Notes

- 1) TC: Total capacity [kW]
H: High
M: Medium
L: Low
- 2) Outdoor temperature -7-°C DB / -6-°C WB