

**FXNQ-A**

Unit size	Outdoor °CDB	Indoor air temp.													
		14.0 WB		16.0 WB		18.0 WB		19.0 WB		20.0 WB		22.0 WB		24.0 WB	
		20.0 DB		23.0 DB		26.0 DB		27.0 DB		28.0 DB		30.0 DB		32.0 DB	
		TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
15	35.0	1.1	1.1	1.4	1.3	1.6	1.4	1.7	1.5	1.8	1.4	1.8	1.4	1.9	1.4
20	35.0	1.5	1.4	1.8	1.6	2.1	1.8	2.2	1.9	2.3	1.9	2.4	1.7	2.4	1.8
25	35.0	1.9	1.6	2.3	1.9	2.6	2.1	2.8	2.1	3.0	2.2	3.0	2.1	3.1	2.0
32	35.0	2.4	1.9	2.9	2.2	3.4	2.4	3.6	2.6	3.8	2.6	3.9	2.5	4.0	2.5
40	35.0	3.0	2.5	3.6	2.8	4.2	3.3	4.5	3.3	4.7	3.2	4.9	3.1	5.0	3.2
50	35.0	3.8	3.1	4.5	3.5	5.2	3.9	5.6	4.0	5.9	4.0	6.0	3.9	6.2	3.7
63	35.0	4.8	3.8	5.7	4.3	6.6	4.8	7.1	4.9	7.5	4.8	7.7	4.8	7.8	4.8

TC: Total capacity (kW)

SHC Sensible heating capacity (kW)