

Unit size	Fan speed	Indoor air temperature					
		16,0 [°C DB]	18,0 [°C DB]	20,0 [°C DB]	21,0 [°C DB]	22,0 [°C DB]	24,0 [°C DB]
		TC	TC	TC	TC	TC	TC
15	H	2,2	2,1	1,9	1,8	1,7	1,6
	M	Correction factor $-0.84 \times H$					
	L	Correction factor $-0.79 \times H$					
20	H	2,9	2,7	2,5	2,4	2,3	2,1
	M	Correction factor $-0.84 \times H$					
	L	Correction factor $-0.72 \times H$					
25	H	3,7	3,5	3,2	3,1	2,9	2,7
	M	Correction factor $-0.84 \times H$					
	L	Correction factor $-0.72 \times H$					
32	H	4,7	4,3	4,0	3,8	3,7	3,3
	M	Correction factor $-0.85 \times H$					
	L	Correction factor $-0.73 \times H$					
40	H	5,8	5,4	5,0	4,8	4,6	4,2
	M	Correction factor $-0.84 \times H$					
	L	Correction factor $-0.72 \times H$					
50	H	7,3	6,8	6,3	6,0	5,8	5,3
	M	Correction factor $-0.81 \times H$					
	L	Correction factor $-0.65 \times H$					
63	H	9,3	8,7	8,0	7,7	7,3	6,7
	M	Correction factor $-0.79 \times H$					
	L	Correction factor $-0.63 \times H$					
80	H	11,7	10,8	10,0	9,6	9,2	8,4
	M	Correction factor $-0.83 \times H$					
	L	Correction factor $-0.59 \times H$					
100	H	14,6	13,5	12,5	12,0	11,5	10,5
	M	Correction factor $-0.74 \times H$					
	L	Correction factor $-0.48 \times H$					
125	H	18,7	17,3	16,0	15,3	14,7	13,4
	M	Correction factor $-0.80 \times H$					
	L	Correction factor $-0.61 \times H$					
140	H	21,0	19,5	18,0	17,3	16,5	15,1
	M	Correction factor $-0.78 \times H$					
	L	Correction factor $-0.58 \times H$					

Notes

1) TC: Total capacity [kW]

2) Outdoor temperature -7°C DB / -6°C WB