

VRV-5 Heat recovery

Low noise data (level ·1-5·)

	Capacity ratio
LN1	90%
LN2	75%
LN3	60%
LN4	45%
LN5	30%

5HP/ 8HP	Cooling		Heating	
	Sound power [dBA]	Sound pressure [dBA]	Sound power [dBA]	Sound pressure [dBA]
LN1	75	53	76	55
LN2	72	50	73	52
LN3	69	47	70	49
LN4	66	44	67	46
LN5	63	41	64	43

10HP	Cooling		Heating	
	Sound power [dBA]	Sound pressure [dBA]	Sound power [dBA]	Sound pressure [dBA]
LN1	76	55	78	56
LN2	73	52	75	53
LN3	70	49	72	50
LN4	67	46	69	47
LN5	64	43	66	44

12HP	Cooling		Heating	
	Sound power [dBA]	Sound pressure [dBA]	Sound power [dBA]	Sound pressure [dBA]
LN1	79	58	80	58
LN2	76	55	77	55
LN3	73	52	74	52
LN4	70	49	71	49
LN5	67	46	68	46

14HP	Cooling		Heating	
	Sound power [dBA]	Sound pressure [dBA]	Sound power [dBA]	Sound pressure [dBA]
LN1	76	53	81	58
LN2	73	50	78	55
LN3	70	47	75	52
LN4	67	44	72	49
LN5	64	41	69	46

16HP	Cooling		Heating	
	Sound power [dBA]	Sound pressure [dBA]	Sound power [dBA]	Sound pressure [dBA]
LN1	81	58	84	62
LN2	78	55	82	59
LN3	75	52	80	56
LN4	72	49	77	53
LN5	69	46	74	50