

RXYSA-BV1
RXYSA-BY1

Connection ratio [%]

Outdoor air temperature [°C DB]	Cooling capacity [kW]						
	Indoor intake air temperature [°C WB]						
	14.0	16.0	18.0	19.0	20.0	22.0	24.0
130%	10	6.77	8.47	11.6	12.8	13.2	14.9
	12	6.77	8.47	11.6	12.8	13.2	14.9
	14	6.77	8.47	11.6	12.8	13.2	14.9
	16	6.77	8.47	11.6	12.8	13.2	14.9
	18	6.77	8.47	11.6	12.8	13.2	14.9
	20	6.77	8.47	11.6	12.8	13.2	14.9
	21	6.77	8.47	11.6	12.8	13.2	14.9
	23	6.77	8.47	11.6	12.8	13.2	14.9
	25	6.77	8.47	11.6	12.8	13.2	14.9
	27	6.77	8.47	11.6	12.8	13.2	14.9
	29	6.77	8.47	11.6	12.8	13.2	14.9
	31	6.77	8.47	11.6	12.7	13.1	14.8
	33	6.77	8.47	11.6	12.6	13.0	14.6
	35	6.77	8.47	11.6	12.4	12.8	14.4
	37	6.77	8.47	11.6	12.1	12.5	14.2
120%	39	6.77	8.47	11.3	11.7	12.1	13.8
	10	6.25	7.82	10.7	12.0	12.9	14.4
	12	6.25	7.82	10.7	12.0	12.9	14.4
	14	6.25	7.82	10.7	12.0	12.9	14.4
	16	6.25	7.82	10.7	12.0	12.9	14.4
	18	6.25	7.82	10.7	12.0	12.9	14.4
	20	6.25	7.82	10.7	12.0	12.9	14.4
	21	6.25	7.82	10.7	12.0	12.9	14.4
	23	6.25	7.82	10.7	12.0	12.9	14.4
	25	6.25	7.82	10.7	12.0	12.9	14.4
	27	6.25	7.82	10.7	12.0	12.9	14.4
	29	6.25	7.82	10.7	12.0	12.9	14.4
	31	6.25	7.82	10.7	12.0	12.8	14.3
	33	6.25	7.82	10.7	12.0	12.7	14.2
	35	6.25	7.82	10.7	12.0	12.5	14.0
110%	37	6.25	7.82	10.7	11.8	12.2	13.7
	39	6.25	7.82	10.7	11.4	11.8	13.3
	10	5.72	7.17	9.82	11.0	12.2	14.0
	12	5.72	7.17	9.82	11.0	12.2	14.0
	14	5.72	7.17	9.82	11.0	12.2	14.0
	16	5.72	7.17	9.82	11.0	12.2	14.0
	18	5.72	7.17	9.82	11.0	12.2	14.0
	20	5.72	7.17	9.82	11.0	12.2	14.0
	21	5.72	7.17	9.82	11.0	12.2	14.0
	23	5.72	7.17	9.82	11.0	12.2	14.0
	25	5.72	7.17	9.82	11.0	12.2	14.0
	27	5.72	7.17	9.82	11.0	12.2	14.0
	29	5.72	7.17	9.82	11.0	12.2	14.0
	31	5.72	7.17	9.82	11.0	12.2	13.9
	33	5.72	7.17	9.82	11.0	12.2	13.7
100%	35	5.72	7.17	9.82	11.0	12.1	13.5
	37	5.72	7.17	9.82	11.0	11.9	13.3
	39	5.72	7.17	9.82	11.0	11.5	12.9
	10	5.20	6.52	8.93	10.0	11.1	13.5
	12	5.20	6.52	8.93	10.0	11.1	13.5
	14	5.20	6.52	8.93	10.0	11.1	13.5
	16	5.20	6.52	8.93	10.0	11.1	13.5
	18	5.20	6.52	8.93	10.0	11.1	13.5
	20	5.20	6.52	8.93	10.0	11.1	13.5
	21	5.20	6.52	8.93	10.0	11.1	13.5
	23	5.20	6.52	8.93	10.0	11.1	13.5
	25	5.20	6.52	8.93	10.0	11.1	13.5
	27	5.20	6.52	8.93	10.0	11.1	13.5
	29	5.20	6.52	8.93	10.0	11.1	13.5
	31	5.20	6.52	8.93	10.0	11.1	13.4
90%	33	5.20	6.52	8.93	10.0	11.1	13.3
	35	5.20	6.52	8.93	10.0	11.1	13.1
	37	5.20	6.52	8.93	10.0	11.1	12.8
	39	5.20	6.52	8.93	10.0	11.1	12.4
	10	4.68	5.87	8.04	9.02	10.0	13.1
	12	4.68	5.87	8.04	9.02	10.0	13.1
	14	4.68	5.87	8.04	9.02	10.0	13.1
	16	4.68	5.87	8.04	9.02	10.0	13.1
	18	4.68	5.87	8.04	9.02	10.0	13.1
	20	4.68	5.87	8.04	9.02	10.0	13.1
	21	4.68	5.87	8.04	9.02	10.0	13.1
	23	4.68	5.87	8.04	9.02	10.0	13.1