

RXYSA-BV1
RXYSA-BY1

Connection ratio [%]	Outdoor air temperature [°C DB]	Cooling capacity [kW]						
		Indoor intake air temperature [°C WB]						
		14.0	16.0	18.0	19.0	20.0	22.0	24.0
130%	10	7.83	9.81	13.4	14.8	15.3	17.2	18.3
	12	7.83	9.81	13.4	14.8	15.3	17.2	18.3
	14	7.83	9.81	13.4	14.8	15.3	17.2	18.3
	16	7.83	9.81	13.4	14.8	15.3	17.2	18.3
	18	7.83	9.81	13.4	14.8	15.3	17.2	18.3
	20	7.83	9.81	13.4	14.8	15.3	17.2	18.3
	21	7.83	9.81	13.4	14.8	15.3	17.2	18.3
	23	7.83	9.81	13.4	14.8	15.3	17.2	18.3
	25	7.83	9.81	13.4	14.8	15.3	17.2	18.3
	27	7.83	9.81	13.4	14.8	15.3	17.2	18.3
	29	7.83	9.81	13.4	14.8	15.3	17.2	18.3
	31	7.83	9.81	13.4	14.7	15.2	17.1	18.2
	33	7.83	9.81	13.4	14.5	15.0	16.9	18.0
	35	7.83	9.81	13.4	14.3	14.8	16.7	17.8
	37	7.83	9.81	13.4	14.0	14.5	16.4	17.5
	39	7.83	9.81	13.1	13.6	14.1	16.0	17.1
120%	10	7.23	9.05	12.4	13.9	14.9	16.7	17.7
	12	7.23	9.05	12.4	13.9	14.9	16.7	17.7
	14	7.23	9.05	12.4	13.9	14.9	16.7	17.7
	16	7.23	9.05	12.4	13.9	14.9	16.7	17.7
	18	7.23	9.05	12.4	13.9	14.9	16.7	17.7
	20	7.23	9.05	12.4	13.9	14.9	16.7	17.7
	21	7.23	9.05	12.4	13.9	14.9	16.7	17.7
	23	7.23	9.05	12.4	13.9	14.9	16.7	17.7
	25	7.23	9.05	12.4	13.9	14.9	16.7	17.7
	27	7.23	9.05	12.4	13.9	14.9	16.7	17.7
	29	7.23	9.05	12.4	13.9	14.9	16.7	17.7
	31	7.23	9.05	12.4	13.9	14.8	16.6	17.6
	33	7.23	9.05	12.4	13.9	14.7	16.4	17.4
	35	7.23	9.05	12.4	13.9	14.4	16.2	17.2
	37	7.23	9.05	12.4	13.7	14.1	15.9	16.9
	39	7.23	9.05	12.4	13.2	13.7	15.4	16.5
110%	10	6.62	8.30	11.4	12.8	14.1	16.2	17.1
	12	6.62	8.30	11.4	12.8	14.1	16.2	17.1
	14	6.62	8.30	11.4	12.8	14.1	16.2	17.1
	16	6.62	8.30	11.4	12.8	14.1	16.2	17.1
	18	6.62	8.30	11.4	12.8	14.1	16.2	17.1
	20	6.62	8.30	11.4	12.8	14.1	16.2	17.1
	21	6.62	8.30	11.4	12.8	14.1	16.2	17.1
	23	6.62	8.30	11.4	12.8	14.1	16.2	17.1
	25	6.62	8.30	11.4	12.8	14.1	16.2	17.1
	27	6.62	8.30	11.4	12.8	14.1	16.2	17.1
	29	6.62	8.30	11.4	12.8	14.1	16.1	17.1
	31	6.62	8.30	11.4	12.8	14.1	16.1	17.0
	33	6.62	8.30	11.4	12.8	14.1	15.9	16.8
	35	6.62	8.30	11.4	12.8	14.0	15.7	16.6
	37	6.62	8.30	11.4	12.8	13.7	15.3	16.3
	39	6.62	8.30	11.4	12.8	13.3	14.9	15.8
100%	10	6.02	7.54	10.3	11.6	12.9	15.6	16.5
	12	6.02	7.54	10.3	11.6	12.9	15.6	16.5
	14	6.02	7.54	10.3	11.6	12.9	15.6	16.5
	16	6.02	7.54	10.3	11.6	12.9	15.6	16.5
	18	6.02	7.54	10.3	11.6	12.9	15.6	16.5
	20	6.02	7.54	10.3	11.6	12.9	15.6	16.5
	21	6.02	7.54	10.3	11.6	12.9	15.6	16.5
	23	6.02	7.54	10.3	11.6	12.9	15.6	16.5
	25	6.02	7.54	10.3	11.6	12.9	15.6	16.5
	27	6.02	7.54	10.3	11.6	12.9	15.7	16.5
	29	6.02	7.54	10.3	11.6	12.9	15.6	16.5
	31	6.02	7.54	10.3	11.6	12.9	15.5	16.4
	33	6.02	7.54	10.3	11.6	12.9	15.4	16.2
	35	6.02	7.54	10.3	11.6	12.9	15.1	16.0
	37	6.02	7.54	10.3	11.6	12.9	14.8	15.7
	39	6.02	7.54	10.3	11.6	12.9	14.4	15.2
90%	10	5.42	6.79	9.30	10.4	11.6	15.1	15.9
	12	5.42	6.79	9.30	10.4	11.6	15.1	15.9
	14	5.42	6.79	9.30	10.4	11.6	15.1	15.9
	16	5.42	6.79	9.30	10.4	11.6	15.1	15.9
	18	5.42	6.79	9.30	10.4	11.6	15.1	15.9
	20	5.42	6.79	9.30	10.4	11.6	15.1	15.9
	21	5.42	6.79	9.30	10.4	11.6	15.1	15.9
	23	5.42	6.79	9.30	10.4	11.6	15.1	15.9