

RXYSA-BV1
RXYSA-BY1

Connection ratio [%]

130%

120%

110%

100%

90%

Outdoor air temperature [°C DB]	Cooling capacity [kW]						
	Indoor intake air temperature [°C WB]						
	14.0	16.0	18.0	19.0	20.0	22.0	24.0
10	5.06	7.19	9.66	10.7	12.3	13.5	15.8
12	5.06	7.19	9.66	10.7	12.3	13.5	15.8
14	5.06	7.19	9.66	10.7	12.3	13.5	15.8
16	5.06	7.19	9.66	10.7	12.3	13.5	15.8
18	5.06	7.19	9.66	10.7	12.3	13.5	15.8
20	5.06	7.19	9.66	10.7	12.3	13.5	15.8
21	5.06	7.19	9.66	10.7	12.3	13.5	15.8
23	5.06	7.19	9.66	10.7	12.3	13.5	15.8
25	5.06	7.19	9.66	10.7	12.3	13.5	15.8
27	5.06	7.19	9.66	10.7	12.3	13.5	15.8
29	5.06	7.19	9.66	10.7	12.3	13.5	15.8
31	5.06	7.19	9.66	10.7	12.3	13.4	15.7
33	5.06	7.19	9.66	10.7	12.3	13.3	15.6
35	5.06	7.19	9.66	10.7	12.2	13.1	15.4
37	5.06	7.19	9.66	10.7	11.9	12.8	15.1
39	5.06	7.19	9.66	10.7	11.5	12.4	14.7
10	4.67	6.63	8.92	9.92	11.4	13.1	15.3
12	4.67	6.63	8.92	9.92	11.4	13.1	15.3
14	4.67	6.63	8.92	9.92	11.4	13.1	15.3
16	4.67	6.63	8.92	9.92	11.4	13.1	15.3
18	4.67	6.63	8.92	9.92	11.4	13.1	15.3
20	4.67	6.63	8.92	9.92	11.4	13.1	15.3
21	4.67	6.63	8.92	9.92	11.4	13.1	15.3
23	4.67	6.63	8.92	9.92	11.4	13.1	15.3
25	4.67	6.63	8.92	9.92	11.4	13.1	15.3
27	4.67	6.63	8.92	9.92	11.4	13.2	15.3
29	4.67	6.63	8.92	9.92	11.4	13.1	15.3
31	4.67	6.63	8.92	9.92	11.4	13.0	15.2
33	4.67	6.63	8.92	9.92	11.4	12.9	15.1
35	4.67	6.63	8.92	9.92	11.4	12.7	14.8
37	4.67	6.63	8.92	9.92	11.4	12.4	14.6
39	4.67	6.63	8.92	9.92	11.2	12.1	14.2
10	4.28	6.08	8.18	9.10	10.4	12.8	14.8
12	4.28	6.08	8.18	9.10	10.4	12.8	14.8
14	4.28	6.08	8.18	9.10	10.4	12.8	14.8
16	4.28	6.08	8.18	9.10	10.4	12.8	14.8
18	4.28	6.08	8.18	9.10	10.4	12.8	14.8
20	4.28	6.08	8.18	9.10	10.4	12.8	14.8
21	4.28	6.08	8.18	9.10	10.4	12.8	14.8
23	4.28	6.08	8.18	9.10	10.4	12.8	14.8
25	4.28	6.08	8.18	9.10	10.4	12.8	14.8
27	4.28	6.08	8.18	9.10	10.4	12.8	14.8
29	4.28	6.08	8.18	9.10	10.4	12.8	14.7
31	4.28	6.08	8.18	9.10	10.4	12.7	14.7
33	4.28	6.08	8.18	9.10	10.4	12.6	14.5
35	4.28	6.08	8.18	9.10	10.4	12.4	14.3
37	4.28	6.08	8.18	9.10	10.4	12.1	14.0
39	4.28	6.08	8.18	9.10	10.4	11.7	13.7
10	3.89	5.53	7.43	8.27	9.47	11.8	14.2
12	3.89	5.53	7.43	8.27	9.47	11.8	14.2
14	3.89	5.53	7.43	8.27	9.47	11.8	14.2
16	3.89	5.53	7.43	8.27	9.47	11.8	14.2
18	3.89	5.53	7.43	8.27	9.47	11.8	14.2
20	3.89	5.53	7.43	8.27	9.47	11.8	14.2
21	3.89	5.53	7.43	8.27	9.47	11.8	14.2
23	3.89	5.53	7.43	8.27	9.47	11.8	14.2
25	3.89	5.53	7.43	8.27	9.47	11.8	14.2
27	3.89	5.53	7.43	8.27	9.47	11.8	14.2
29	3.89	5.53	7.43	8.27	9.47	11.8	14.2
31	3.89	5.53	7.43	8.27	9.47	11.8	14.1
33	3.89	5.53	7.43	8.27	9.47	11.8	14.0
35	3.89	5.53	7.43	8.27	9.47	11.8	13.8
37	3.89	5.53	7.43	8.27	9.47	11.7	13.5
39	3.89	5.53	7.43	8.27	9.47	11.4	13.2
10	3.50	4.98	6.69	7.44	8.52	10.6	13.7
12	3.50	4.98	6.69	7.44	8.52	10.6	13.7
14	3.50	4.98	6.69	7.44	8.52	10.6	13.7
16	3.50	4.98	6.69	7.44	8.52	10.6	13.7
18	3.50	4.98	6.69	7.44	8.52	10.6	13.7
20	3.50	4.98	6.69	7.44	8.52	10.6	13.7
21	3.50	4.98	6.69	7.44	8.52	10.6	13.7
23	3.50	4.98	6.69	7.44	8.52	10.6	13.7