

RXYSA-BV1

RXYSA-BY1

Connection ratio [%]	Outdoor air temperature [°C DB]	Cooling capacity [kW]						
		Indoor intake air temperature [°C WB]						
		14.0	16.0	18.0	19.0	20.0	22.0	24.0
130%	10	6.48	9.21	12.4	13.8	15.8	17.3	20.3
	12	6.48	9.21	12.4	13.8	15.8	17.3	20.3
	14	6.48	9.21	12.4	13.8	15.8	17.3	20.3
	16	6.48	9.21	12.4	13.8	15.8	17.3	20.3
	18	6.48	9.21	12.4	13.8	15.8	17.3	20.3
	20	6.48	9.21	12.4	13.8	15.8	17.3	20.3
	21	6.48	9.21	12.4	13.8	15.8	17.3	20.3
	23	6.48	9.21	12.4	13.8	15.8	17.3	20.3
	25	6.48	9.21	12.4	13.8	15.8	17.3	20.3
	27	6.48	9.21	12.4	13.8	15.8	17.3	20.3
	29	6.48	9.21	12.4	13.8	15.8	17.3	20.2
	31	6.48	9.21	12.4	13.8	15.8	17.2	20.1
	33	6.48	9.21	12.4	13.8	15.8	17.0	20.0
	35	6.48	9.21	12.4	13.8	15.6	16.7	19.7
	37	6.48	9.21	12.4	13.8	15.2	16.4	19.3
	39	6.48	9.21	12.4	13.8	14.8	15.9	18.9
120%	10	5.98	8.50	11.4	12.7	14.6	16.8	19.6
	12	5.98	8.50	11.4	12.7	14.6	16.8	19.6
	14	5.98	8.50	11.4	12.7	14.6	16.8	19.6
	16	5.98	8.50	11.4	12.7	14.6	16.8	19.6
	18	5.98	8.50	11.4	12.7	14.6	16.8	19.6
	20	5.98	8.50	11.4	12.7	14.6	16.8	19.6
	21	5.98	8.50	11.4	12.7	14.6	16.8	19.6
	23	5.98	8.50	11.4	12.7	14.6	16.8	19.6
	25	5.98	8.50	11.4	12.7	14.6	16.8	19.6
	27	5.98	8.50	11.4	12.7	14.6	16.8	19.6
	29	5.98	8.50	11.4	12.7	14.6	16.8	19.6
	31	5.98	8.50	11.4	12.7	14.6	16.7	19.5
	33	5.98	8.50	11.4	12.7	14.6	16.5	19.3
	35	5.98	8.50	11.4	12.7	14.6	16.3	19.0
	37	5.98	8.50	11.4	12.7	14.6	15.9	18.7
	39	5.98	8.50	11.4	12.7	14.4	15.5	18.2
110%	10	5.48	7.79	10.5	11.7	13.3	16.4	18.9
	12	5.48	7.79	10.5	11.7	13.3	16.4	18.9
	14	5.48	7.79	10.5	11.7	13.3	16.4	18.9
	16	5.48	7.79	10.5	11.7	13.3	16.4	18.9
	18	5.48	7.79	10.5	11.7	13.3	16.4	18.9
	20	5.48	7.79	10.5	11.7	13.3	16.4	18.9
	21	5.48	7.79	10.5	11.7	13.3	16.4	18.9
	23	5.48	7.79	10.5	11.7	13.3	16.4	18.9
	25	5.48	7.79	10.5	11.7	13.3	16.4	18.9
	27	5.48	7.79	10.5	11.7	13.3	16.4	18.9
	29	5.48	7.79	10.5	11.7	13.3	16.4	18.9
	31	5.48	7.79	10.5	11.7	13.3	16.3	18.8
	33	5.48	7.79	10.5	11.7	13.3	16.1	18.6
	35	5.48	7.79	10.5	11.7	13.3	15.8	18.4
	37	5.48	7.79	10.5	11.7	13.3	15.5	18.0
	39	5.48	7.79	10.5	11.7	13.3	15.0	17.5
100%	10	4.98	7.08	9.52	10.6	12.1	15.1	18.2
	12	4.98	7.08	9.52	10.6	12.1	15.1	18.2
	14	4.98	7.08	9.52	10.6	12.1	15.1	18.2
	16	4.98	7.08	9.52	10.6	12.1	15.1	18.2
	18	4.98	7.08	9.52	10.6	12.1	15.1	18.2
	20	4.98	7.08	9.52	10.6	12.1	15.1	18.2
	21	4.98	7.08	9.52	10.6	12.1	15.1	18.2
	23	4.98	7.08	9.52	10.6	12.1	15.1	18.2
	25	4.98	7.08	9.52	10.6	12.1	15.1	18.2
	27	4.98	7.08	9.52	10.6	12.1	15.1	18.2
	29	4.98	7.08	9.52	10.6	12.1	15.1	18.2
	31	4.98	7.08	9.52	10.6	12.1	15.1	18.1
	33	4.98	7.08	9.52	10.6	12.1	15.1	17.9
	35	4.98	7.08	9.52	10.6	12.1	15.1	17.7
	37	4.98	7.08	9.52	10.6	12.1	15.0	17.3
	39	4.98	7.08	9.52	10.6	12.1	14.6	16.9
90%	10	4.49	6.37	8.57	9.53	10.9	13.6	17.6
	12	4.49	6.37	8.57	9.53	10.9	13.6	17.6
	14	4.49	6.37	8.57	9.53	10.9	13.6	17.6
	16	4.49	6.37	8.57	9.53	10.9	13.6	17.6
	18	4.49	6.37	8.57	9.53	10.9	13.6	17.6
	20	4.49	6.37	8.57	9.53	10.9	13.6	17.6
	21	4.49	6.37	8.57	9.53	10.9	13.6	17.6
	23	4.49	6.37	8.57	9.53	10.9	13.6	17.6