

RXYS-A-BV1

RXYS-A-BY1

Connection ratio [%]	Outdoor air temperature [°C DB]	Cooling capacity [kW]						
		Indoor intake air temperature [°C WB]						
		14.0	16.0	18.0	19.0	20.0	22.0	24.0
130%	10	9.31	11.6	13.0	13.6	14.0	14.9	15.8
	12	9.31	11.6	13.0	13.6	14.0	14.9	15.8
	14	9.31	11.6	13.0	13.6	14.0	14.9	15.8
	16	9.31	11.6	13.0	13.6	14.0	14.9	15.8
	18	9.31	11.6	13.0	13.6	14.0	14.9	15.8
	20	9.31	11.6	13.0	13.6	14.0	14.9	15.8
	21	9.31	11.6	13.0	13.6	14.0	14.9	15.8
	23	9.31	11.6	13.0	13.6	14.0	14.9	15.8
	25	9.31	11.6	13.0	13.6	14.0	14.9	15.8
	27	9.31	11.6	13.0	13.6	14.0	14.9	15.8
	29	9.31	11.6	13.0	13.6	13.9	14.9	15.8
	31	9.31	11.6	12.9	13.5	13.9	14.8	15.7
	33	9.31	11.6	12.8	13.4	13.7	14.7	15.6
	35	9.31	11.6	12.6	13.2	13.5	14.5	15.4
	37	9.31	11.6	12.3	12.9	13.2	14.2	15.1
	39	9.31	11.3	12.0	12.5	12.9	13.8	14.7
120%	10	8.60	10.7	12.7	13.2	13.6	14.4	15.3
	12	8.60	10.7	12.7	13.2	13.6	14.4	15.3
	14	8.60	10.7	12.7	13.2	13.6	14.4	15.3
	16	8.60	10.7	12.7	13.2	13.6	14.4	15.3
	18	8.60	10.7	12.7	13.2	13.6	14.4	15.3
	20	8.60	10.7	12.7	13.2	13.6	14.4	15.3
	21	8.60	10.7	12.7	13.2	13.6	14.4	15.3
	23	8.60	10.7	12.7	13.2	13.6	14.4	15.3
	25	8.60	10.7	12.7	13.2	13.6	14.4	15.3
	27	8.60	10.7	12.7	13.3	13.6	14.4	15.3
	29	8.60	10.7	12.7	13.2	13.6	14.4	15.3
	31	8.60	10.7	12.6	13.1	13.5	14.3	15.2
	33	8.60	10.7	12.5	13.0	13.3	14.2	15.1
	35	8.60	10.7	12.3	12.8	13.1	14.0	14.9
	37	8.60	10.7	12.0	12.5	12.9	13.7	14.6
	39	8.60	10.7	11.6	12.2	12.5	13.4	14.2
110%	10	7.88	9.79	11.7	12.9	13.2	14.0	14.8
	12	7.88	9.79	11.7	12.9	13.2	14.0	14.8
	14	7.88	9.79	11.7	12.9	13.2	14.0	14.8
	16	7.88	9.79	11.7	12.9	13.2	14.0	14.8
	18	7.88	9.79	11.7	12.9	13.2	14.0	14.8
	20	7.88	9.79	11.7	12.9	13.2	14.0	14.8
	21	7.88	9.79	11.7	12.9	13.2	14.0	14.8
	23	7.88	9.79	11.7	12.9	13.2	14.0	14.8
	25	7.88	9.79	11.7	12.9	13.2	14.0	14.8
	27	7.88	9.79	11.7	12.9	13.2	14.0	14.8
	29	7.88	9.79	11.7	12.9	13.2	14.0	14.8
	31	7.88	9.79	11.7	12.8	13.1	13.9	14.7
	33	7.88	9.79	11.7	12.7	13.0	13.7	14.5
	35	7.88	9.79	11.7	12.5	12.8	13.5	14.3
	37	7.88	9.79	11.7	12.2	12.5	13.3	14.1
	39	7.88	9.79	11.3	11.8	12.1	12.9	13.7
100%	10	7.16	8.90	10.6	12.1	12.8	13.5	14.3
	12	7.16	8.90	10.6	12.1	12.8	13.5	14.3
	14	7.16	8.90	10.6	12.1	12.8	13.5	14.3
	16	7.16	8.90	10.6	12.1	12.8	13.5	14.3
	18	7.16	8.90	10.6	12.1	12.8	13.5	14.3
	20	7.16	8.90	10.6	12.1	12.8	13.5	14.3
	21	7.16	8.90	10.6	12.1	12.8	13.5	14.3
	23	7.16	8.90	10.6	12.1	12.8	13.5	14.3
	25	7.16	8.90	10.6	12.1	12.8	13.5	14.3
	27	7.16	8.90	10.6	12.1	12.8	13.5	14.3
	29	7.16	8.90	10.6	12.1	12.8	13.5	14.2
	31	7.16	8.90	10.6	12.1	12.7	13.4	14.2
	33	7.16	8.90	10.6	12.1	12.6	13.3	14.0
	35	7.16	8.90	10.6	12.1	12.4	13.1	13.8
	37	7.16	8.90	10.6	11.8	12.1	12.8	13.5
	39	7.16	8.90	10.6	11.5	11.7	12.4	13.2
90%	10	6.45	8.01	9.54	10.9	11.7	13.1	13.7
	12	6.45	8.01	9.54	10.9	11.7	13.1	13.7
	14	6.45	8.01	9.54	10.9	11.7	13.1	13.7
	16	6.45	8.01	9.54	10.9	11.7	13.1	13.7
	18	6.45	8.01	9.54	10.9	11.7	13.1	13.7
	20	6.45	8.01	9.54	10.9	11.7	13.1	13.7
	21	6.45	8.01	9.54	10.9	11.7	13.1	13.7
	23	6.45	8.01	9.54	10.9	11.7	13.1	13.7

4D127873A