

RXYS-A-BV1
RXYS-A-BY1

Connection ratio [%]	Outdoor air temperature [°C DB]	Cooling capacity [kW]						
		Indoor intake air temperature [°C WB]						
		14.0	16.0	18.0	19.0	20.0	22.0	24.0
130%	10	11.9	14.8	16.7	17.4	17.9	19.1	20.3
	12	11.9	14.8	16.7	17.4	17.9	19.1	20.3
	14	11.9	14.8	16.7	17.4	17.9	19.1	20.3
	16	11.9	14.8	16.7	17.4	17.9	19.1	20.3
	18	11.9	14.8	16.7	17.4	17.9	19.1	20.3
	20	11.9	14.8	16.7	17.4	17.9	19.1	20.3
	21	11.9	14.8	16.7	17.4	17.9	19.1	20.3
	23	11.9	14.8	16.7	17.4	17.9	19.1	20.3
	25	11.9	14.8	16.7	17.4	17.9	19.1	20.3
	27	11.9	14.8	16.7	17.4	17.9	19.1	20.3
	29	11.9	14.8	16.7	17.4	17.8	19.0	20.2
	31	11.9	14.8	16.6	17.3	17.7	18.9	20.1
	33	11.9	14.8	16.4	17.1	17.6	18.8	20.0
	35	11.9	14.8	16.1	16.9	17.3	18.5	19.7
	37	11.9	14.8	15.8	16.5	17.0	18.2	19.4
	39	11.9	14.5	15.3	16.0	16.5	17.7	18.9
120%	10	11.0	13.7	16.3	17.0	17.4	18.5	19.6
	12	11.0	13.7	16.3	17.0	17.4	18.5	19.6
	14	11.0	13.7	16.3	17.0	17.4	18.5	19.6
	16	11.0	13.7	16.3	17.0	17.4	18.5	19.6
	18	11.0	13.7	16.3	17.0	17.4	18.5	19.6
	20	11.0	13.7	16.3	17.0	17.4	18.5	19.6
	21	11.0	13.7	16.3	17.0	17.4	18.5	19.6
	23	11.0	13.7	16.3	17.0	17.4	18.5	19.6
	25	11.0	13.7	16.3	17.0	17.4	18.5	19.6
	27	11.0	13.7	16.3	17.0	17.4	18.5	19.6
	29	11.0	13.7	16.3	16.9	17.4	18.5	19.6
	31	11.0	13.7	16.2	16.8	17.3	18.4	19.5
	33	11.0	13.7	16.0	16.7	17.1	18.2	19.3
	35	11.0	13.7	15.7	16.4	16.8	17.9	19.0
	37	11.0	13.7	15.4	16.1	16.5	17.6	18.7
	39	11.0	13.7	14.9	15.6	16.0	17.1	18.2
110%	10	10.1	12.5	14.9	16.5	16.9	17.9	18.9
	12	10.1	12.5	14.9	16.5	16.9	17.9	18.9
	14	10.1	12.5	14.9	16.5	16.9	17.9	18.9
	16	10.1	12.5	14.9	16.5	16.9	17.9	18.9
	18	10.1	12.5	14.9	16.5	16.9	17.9	18.9
	20	10.1	12.5	14.9	16.5	16.9	17.9	18.9
	21	10.1	12.5	14.9	16.5	16.9	17.9	18.9
	23	10.1	12.5	14.9	16.5	16.9	17.9	18.9
	25	10.1	12.5	14.9	16.5	16.9	17.9	18.9
	27	10.1	12.5	14.9	16.5	16.9	17.9	18.9
	29	10.1	12.5	14.9	16.5	16.9	17.9	18.9
	31	10.1	12.5	14.9	16.4	16.8	17.8	18.8
	33	10.1	12.5	14.9	16.2	16.6	17.6	18.6
	35	10.1	12.5	14.9	16.0	16.3	17.4	18.4
	37	10.1	12.5	14.9	15.6	16.0	17.0	18.0
	39	10.1	12.5	14.5	15.1	15.5	16.5	17.5
100%	10	9.18	11.4	13.6	15.5	16.4	17.3	18.3
	12	9.18	11.4	13.6	15.5	16.4	17.3	18.3
	14	9.18	11.4	13.6	15.5	16.4	17.3	18.3
	16	9.18	11.4	13.6	15.5	16.4	17.3	18.3
	18	9.18	11.4	13.6	15.5	16.4	17.3	18.3
	20	9.18	11.4	13.6	15.5	16.4	17.3	18.3
	21	9.18	11.4	13.6	15.5	16.4	17.3	18.3
	23	9.18	11.4	13.6	15.5	16.4	17.3	18.3
	25	9.18	11.4	13.6	15.5	16.4	17.3	18.3
	27	9.18	11.4	13.6	15.5	16.4	17.3	18.3
	29	9.18	11.4	13.6	15.5	16.4	17.3	18.2
	31	9.18	11.4	13.6	15.5	16.3	17.2	18.1
	33	9.18	11.4	13.6	15.5	16.1	17.0	18.0
	35	9.18	11.4	13.6	15.5	15.9	16.8	17.7
	37	9.18	11.4	13.6	15.1	15.5	16.4	17.3
	39	9.18	11.4	13.6	14.7	15.0	15.9	16.9
90%	10	8.26	10.3	12.2	14.0	15.0	16.8	17.6
	12	8.26	10.3	12.2	14.0	15.0	16.8	17.6
	14	8.26	10.3	12.2	14.0	15.0	16.8	17.6
	16	8.26	10.3	12.2	14.0	15.0	16.8	17.6
	18	8.26	10.3	12.2	14.0	15.0	16.8	17.6
	20	8.26	10.3	12.2	14.0	15.0	16.8	17.6
	21	8.26	10.3	12.2	14.0	15.0	16.8	17.6
	23	8.26	10.3	12.2	14.0	15.0	16.8	17.6