

EKVDX-A

		Indoor air temperature					
		16.0 [°C DB]	18.0 [°C DB]	20.0 [°C DB]	21.0 [°C DB]	22.0 [°C DB]	24.0 [°C DB]
Indoor unit combinations	Fan speed	TC	TC	TC	TC	TC	TC
EKVDX32 / VAM500	UH	4.9	4.5	4.2	4.0	3.9	3.5
	H	Correction factor ·0.85 x UH·					
EKVDX50 / VAM650	UH	5.9	5.5	5.1	4.9	4.7	4.3
	H	Correction factor ·0.91 x UH·					
EKVDX50 / VAM800	UH	8.0	6.8	6.9	6.6	6.4	5.8
	H	Correction factor ·0.84 x UH·					
EKVDX80 / VAM1000	UH	8.2	7.6	7.0	6.7	6.4	5.9
	H	Correction factor ·0.90 x UH·					
EKVDX100 / VAM1500	UH	12.6	11.7	10.8	10.4	9.9	9.1
	H	Correction factor ·0.89 x UH·					
EKVDX100 / VAM2000	UH	15.2	14.0	13.0	12.5	12.0	10.9
	H	Correction factor ·0.90 x UH·					

Notes

1. TC: Total capacity [kW]
2. Outdoor temperature ·7·°C DB / ·6·°C WB

3D127979