

EKVDX-A

		Temperatura de aire interior													
		14.0 [°C WB]		16.0 [°C WB]		18.0 [°C WB]		19.0 [°C WB]		20.0 [°C WB]		22.0 [°C WB]		24.0 [°C WB]	
		20.0 [°C DB]		23.0 [°C DB]		26.0 [°C DB]		27.0 [°C DB]		28.0 [°C DB]		30.0 [°C DB]		32.0 [°C DB]	
Combinaciones de unidades interiores	Velocidad del ventilador	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
EKVDX32 / VAM500	UH	2.0	1.7	2.6	1.9	3.1	2.3	3.4	2.4	3.7	2.5	4.3	2.6	5.0	2.8
	H	Factor de corrección 0.79 x UH													
EKVDX50 / VAM650	UH	2.7	2.2	3.6	2.7	4.4	3.1	4.8	3.2	5.2	3.4	6.1	3.5	7.0	3.7
	H	Factor de corrección 0.86 x UH													
EKVDX50 / VAM800	UH	3.1	2.7	4.1	3.3	5.0	3.8	5.5	3.9	6.0	4.1	7.0	4.3	8.1	4.5
	H	Factor de corrección 0.80 x UH													
EKVDX80 / VAM1000	UH	3.2	3.1	4.2	3.7	5.2	4.4	5.7	4.6	6.2	4.8	7.3	5.1	8.5	5.3
	H	Factor de corrección 0.79 x UH													
EKVDX100 / VAM1500	UH	5.4	4.8	7.0	5.8	8.7	6.7	9.5	7.0	10.3	7.3	12.2	7.8	14.1	8.2
	H	Factor de corrección 0.93 x UH													
EKVDX100 / VAM2000	UH	6.4	6.2	8.3	7.6	10.2	8.9	11.2	9.2	12.2	9.5	14.4	10.2	16.6	10.8
	H	Factor de corrección 0.94 x UH													

- Notas
- 1. TC: Capacidad total [kW]
SHC: Capacidad de sensibilidad al calor [kW]
 - 2. Temperatura exterior -35°C DB