Available options for ·VAM*J8*· models in combination with ·EKVDX*·

Item								
			VAM500J8VEB	VAM650J8VEB	VAM800J8VEB VAM800J8VEB9	VAM1000J8VEB VAM1000J8VEB9	VAM1500J8VEB VAM1500J8VEB9	VAM2000J8VEB VAM2000J8VEB9
Adaptor PCB	For heaters		BRP4A50A					
	Mounting plate		- - - -	EKMP65VAM (2)	- - - -		EKMPVAM (1)	
Miscellaneous	Plenum chamber	Model	- - - -				EKPLEN200 (3)	
		Outside diameter [mm]					Ø350	
	High-efficiency filter (see note ·4·)	ePM10 70% (M6)	EKAFVJ50F6	EKAFVJ65F6	EKAFVJ100F6		EKAFVJ100F6 x 2	
		ePM1 60% (F7)	EKAFVJ50F7	EKAFVJ65F7	EKAFVJ100F7		EKAFVJ100F7 x 2	
		ePM1 70% (F8)	EKAFVJ50F8	EKAFVJ65F8	EKAFVJ100F8		EKAFVJ100F8 x 2	
CO2 Sensor			BRYMA65		BRYMA100		BRYMA200	

Notes

1. To install an adaptor PCB on ·VAM1500J/VAM2000J· units, mounting plate ·EKMPVAM· is required.
2. To install an adaptor PCB on ·VAM650J· units, mounting plate ·EKMP65VAM· is required.
3. Plenum chamber to merge either ·2· air inlets or ·2· air outlets. Up to ·4· plenum chambers can be connected.
4. If you order 1 filter set, you can use it for either supply side or exhaust side. To provide both sides with filters, 2 filter sets are required.