



# Wall mounted unit

FTXM-M

**BLUEEVOLUTION**



Practically inaudible



2 area intelligent eye



3-D air flow



Flash Streamer



Online controller  
via app

## Attractive, wall mounted design with perfect indoor air quality

- › Practically inaudible: the unit runs so quietly, you will almost forget it is there.
- › Fresher, cleaner air thanks to Daikin's Flash Streamer technology: you can breathe deep with no worries about impure air
- › 2 area intelligent eye: air flow is sent to a zone other than where the person is located at that moment; if no people are detected, the unit will automatically switch over to the energy-ef-

- › efficient setting.
- › 3-D air flow combines vertical and horizontal auto swing to circulate a stream of warm or cool air right to the corners of even large spaces
- › Online controller (optional): control your indoor from any location with an app, via your local network or internet and keep an overview on your energy consumption

# FTXM-M + RXM-M




Indoor unit		FTXM	20M	25M	35M	42M	50M	60M	71M	
Casing	Colour		White							
Dimensions	Unit	HeightxWidthxDepth	294x811x272				300x1,040x295			
Sound power level	Cooling	dB(A)	57		60		60		61	
	Heating	dB(A)	54		60		59		61	
Sound pressure level	Cooling	High/Low/Silent operation	41/25/19		45/29/19		45/30/21		46/37/34	
	Heating	High/Low/Silent operation	39/26/20		39/27/20		39/28/20		45/29/21	
Control systems	Infrared remote control		ARC466A33							
	Wired remote control		BRC944B2 / BRC073A1				BRC944B2 / BRC073			
Refrigerant	Type		R-32							
	GWP		-							

Efficiency data		FTXM + RXM	20M + 20M	25M + 25M	35M + 35M	42M + 42M	50M + 50M	60M + 60M	71M + 71M		
Cooling capacity	Min./Nom./Max.	kW	1.3/2.0/2.6	1.3/2.5/3.2	1.4/3.40/4.0	1.7/4.2/5.0	1.7/5.00/5.3	1.9/6.00/6.7	2.3/7.10/8.5		
Heating capacity	Min./Nom./Max.	kW	1.3/2.50/3.5	1.3/2.8/4.70	1.4/4.00/5.2	1.7/5.40/6.0	1.7/5.8/6.5	1.7/7.00/8.0	2.30/8.20/10.20		
Power input	Cooling	Min./Nom./Max.	0.27/0.44/0.63	0.27/0.56/0.78	0.31/0.80/1.04	0.43/1.12/1.47	-/1.36/-	0.30/1.77/2.30	0.49/2.12/3.44		
	Heating	Min./Nom./Max.	0.24/0.50/0.91	0.24/0.56/1.22	0.32/0.99/1.67	0.38/1.31/1.89	-/1.45/-	0.27/1.94/2.40	0.45/2.25/3.51		
Seasonal efficiency (according to EN14825)	Cooling	Energy label	A+++								
		Pdesign	2.00	2.50	3.40	4.20	5.00	6.00	7.10		
		SEER	8.53	8.52	8.51	7.50	7.33	6.90	6.11		
	Heating (Average climate)	Annual energy consumption	kWh	83	103	140	196	239	304	407	
		Energy label		A+++			A++		A+		A
		Pdesign	kW	2.30	2.40	2.50	4.00	4.60		6.20	
Nominal efficiency	EER	SCOP/A	5.10		4.60		4.30		3.81		
		Annual energy consumption	kWh	632	659	686	1,216	1,400	1,496	2,276	
	COP		4.57	4.50	4.23	3.75	3.68	3.39	3.35		
		Annual energy consumption	kWh	219	278	421	560	679	885	1,172	
Energy label	Cooling/Heating		A/A								

Outdoor unit		RXM	20M	25M	35M	42M	50M	60M	71M	
Dimensions	Unit	HeightxWidthxDepth	550x765x285				735x825x300		734x870x320	
Sound power level	Cooling	dB(A)	59		61		63		64	
	Heating	dB(A)	59		61		62		63	
Sound pressure level	Cooling	High/Low	46/-		49/-		48/-		48/44	
	Heating	High/Low	47/-		49/-		48/-		49/45	
Operation range	Cooling	Ambient	Min.-Max.		°CDB		-10~46			
	Heating	Ambient	Min.-Max.		°CWB		-15~18			
Refrigerant	Type/Charge/GWP	kg/TCO <sub>2</sub> eq	R-32/0.76/0.5/675			R-32/1.30/0.9/675	R-32/1.4/0.9/675	R-32/1.45/1.0/675	R-32/1.15/0.780/675.0	
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240							

**Daikin Europe N.V.** Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



07/16



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.